

FEATURES

- Mechanically or hydraulically set on jointed pipe, coiled tubing, electric wireline or slickline using the Halliburton DPU® downhole power unit
- Sets in a wide range of casing sizes and grades
- Effective setting and sealing in elevated temperatures and pressures
- Available with API 11D1 designation

BENEFITS

- Equipped with a brass mandrel that absorbs greater tensile and impact loads as compared to cast iron mandrel tools
- Tool OD held to a minimum, allowing more clearance between the tool and casing for faster run-in

WELL COMPLETIONS | CEMENTING RETAINERS AND BRIDGE PLUGS

EZ Drill® SVB squeeze packers

Offer enhanced reliability, reduced rig time, and quick drill out

Overview

EZ Drill® SVB (sliding valve brass) squeeze packers can be used for applications, such as wellbore isolation, remedial cementing, and plug and abandonment. Equipped with a rugged brass mandrel, the packer can absorb greater tensile and impact loads. Additionally, the EZ Drill SVB squeeze packer can control flow and differential pressure in either direction by workstring manipulation of the sliding valve inside the tool. Using a conversion kit, EZ Drill SVB squeeze packers can be altered to create a top-drilling bridge plug capable of holding differential pressure in either direction.



HAL40686

EZ Drill® SVB squeeze packer specifications

CASING SIZE	MAXIMUM CASING ID	MINIMUM CASING ID	MAXIMUM TOOL OD	RATED PRESSURE	API 11D1 QUALIFIED
IN. (MM)	IN. (MM)	IN. (MM)	IN. (MM)	PSI (MPA)	
3 1/2 (88.9)	3.240 (82.3)	2.890 (73.4)	2.69 (68.3)	10,000 (69.0)	
4 (101.6)	3.640 (92.5)	3.320 (84.3)	3.12 (79.2)	10,000 (69.0)	
4 1/2 (114.3)	3.920 (99.6)	3.826 (97.2)	3.58 (90.9)	10,000 (69.0)	
4 1/2 (114.3)	4.180 (106.2)	3.910 (99.3)	3.66 (93.0)	10,000 (69.0)	
5 (127.0)	4.560 (115.8)	4.276 (108.6)	3.97 (100.8)	10,000 (69.0)	X
5 1/2 (139.7)	5.040 (128.0)	4.670 (118.6)	4.37 (111.0)	10,000 (69.0)	X
6 (152.4)	5.590 (142.0)	5.220 (132.6)	4.87 (123.7)	10,000 (69.0)	
6 5/8 (168.3)	5.900 (149.9)	5.670 (144.0)	5.32 (135.1)	10,000 (69.0)	
7 (177.8)	6.460 (164.1)	5.900 (149.9)	5.50 (139.7)	10,000 (69.0)	X
7 5/8 (193.7)	7.125 (181.0)	6.500 (165.1)	6.12 (155.4)	10,000 (69.0)	X
8 5/8 (219.1)	7.830 (198.9)	7.310 (185.7)	6.88 (174.8)	10,000 (69.0)	
8 5/8 (219.1)	8.130 (206.5)	7.450 (189.2)	7.00 (177.8)	10,000 (69.0)	
9 5/8 (244.5)	9.063 (230.2)	8.157 (207.2)	7.75 (196.8)	7,500 (51.7)	X
10 3/4 (273.1)	9.500 (241.3)	9.156 (232.6)	8.69 (220.7)	7,500 (51.7)	X
10 3/4 (273.1)	10.192 (258.9)	9.560 (242.8)	9.00 (228.6)	7,500 (51.7)	X
11 3/4 (298.5)	10.406 (264.3)	10.282 (261.2)	9.73 (247.1)	7,500 (51.7)	
11 3/4 (298.5)	11.084 (281.5)	10.438 (265.1)	9.87 (250.7)	7,500 (51.7)	X
13 3/8 (339.7)	12.281 (311.9)	11.907 (302.4)	11.31 (287.3)	5,000 (34.5)	
13 3/8 (339.7)	12.715 (323.0)	12.281 (311.9)	11.68 (296.7)	5,000 (34.5)	X
16 (406.4)	15.250 (387.4)	14.688 (373.1)	13.96 (354.6)	2,500 (17.2)	X
18 5/8 (473.1)	18.000 (457.2)	17.439 (443.0)	16.80 (426.7)	2,500 (17.2)	
20 (508.0)	19.124 (485.7)	17.938 (455.6)	17.24 (437.9)	2,500 (17.2)	

For more information, contact your local Halliburton representative or visit us on the web at www.halliburton.com

Sales of Halliburton products and services will be in accord solely with the terms and conditions contained in the contract between Halliburton and the customer that is applicable to the sale.

H013825 11/24 © 2024 Halliburton. All Rights Reserved.