

XtremeGrip™ System Offers Metal-To-Metal Solution For Complex Deepwater Well

HIGH-PERFORMANCE LINER HANGER SOLVES DEEPWATER WELL CHALLENGES IN ELEVATED TEMPERATURE

GULF OF MEXICO

CHALLENGES

- » Run liner hanger approximately 4,000 ft. with 7 3/4-in. production liner to depth
- » Cement liner hole annulus to isolate production sand
- » Hang liner with a competent liner-top anchor/seal package in extremely deviated well

SOLUTIONS

XtremeGrip™ liner hanger with extrusion rings provides:

- » Metal-to-metal seal with resilient elastomeric seal
- » Increased hang-weight capabilities at elevated temperatures while mitigating risks

RESULTS

- » Over 4,000 ft of casing run to bottom of well deviated to 59 degrees
- » Hanger expanded at pressures modeled by engineers
- » Job completed successfully with ZERO NPT

OVERVIEW

An operator in the Gulf of Mexico had just finished drilling the final section of their most recent deepwater well. The 8 1/2-in. x 9 7/8-in. openhole section was side-tracked through a 10 1/8-in. casing window at a depth of 24,210 ft and reached approximately 28,000 ft total depth. The 10 1/8-in. parent casing was set 34 degrees inclination, and the openhole section reached a maximum deviation of 59 degrees at total depth. A liner hanger was required to reliably run approximately 4,000 ft of 7 3/4-in. production liner to depth, cement the liner hole annulus to isolate the production sand, and hang the liner with a liner-top anchor/seal package – a feat that had not been performed without issue using conventional equipment.

PROJECT DETAILS

While the 81 lb/ft heavy wall parent casing presented a challenge in pre-job models for the traditional VersaFlex® liner hanger system, the XtremeGrip™ system was up for the challenge. What makes the expandable section of this hanger unique is a series of extrusion rings that replace most of the sealing and anchoring elastomers. These rings are similar to the machined ribs found normally on either side of an elastomer, and when expanded, create a metal-to-metal contact that provides high performance at elevated temperatures. With the XtremeGrip system design, thick wall casing is no longer a challenge. This marks the first installation of the XtremeGrip system in the Gulf of Mexico.




HAL121610

PROJECT HIGHLIGHTS

Over 4,000 feet of casing was run to bottom of the deviated well, which reached a maximum deviation of 59 degrees. Halliburton performed the cement job, isolated the formation, and set the hanger. The hanger expanded under pressure very close to what our modeling engineers predicted. The job was a success with ZERO NPT and the customer has placed more orders for the XtremeGrip system for their future GoM jobs.

CASE STUDY



HAL40459

XtremeGrip™ system metal-to-metal anchor feature is designed to provide increased load capability at elevated temperatures

www.halliburton.com

Sales of Halliburton products and services will be in accord solely with the terms and conditions contained in the contract between Halliburton and the customer that is applicable to the sale.

H011546 07/17 © 2017 Halliburton. All Rights Reserved.

HALLIBURTON