

# BARAKLEAN<sup>®</sup>

## CLEANER

### Product Description

BARAKLEAN<sup>®</sup> cleaner is a surfactant solution used for surface cleaning applications. BARAKLEAN can be used to remove water- and oil-based mud residues from pits, tanks, circulating lines and manifolds. BARAKLEAN will remove oil and grease from hard surfaces.

### Applications/Functions

- » Surface equipment cleaning
- » Workshop and warehouse cleaning
- » Hard surface cleaning

### Advantages

- » Strong oil removal and degreasing action
- » Readily disperses oil and grease
- » Easily rinsed and removed

### Typical Properties

- » Appearance: Clear, red liquid
- » Flash point: 210°F (99°C)
- » Specific gravity: 1.01

### Recommended Treatment

A 1:10 dilution in water is suitable for general cleaning of surfaces and equipment. Thick deposits of oil and grease can be removed with a full strength application.

Prolonged exposure may damage painted surfaces.

### Packaging

BARAKLEAN casing cleaner is packaged in 55 gal (208 liter) drums.

BARAKLEAN is a registered trademark of Halliburton. © 2017 Halliburton. All rights reserved. Because the conditions of use of this product are beyond the seller's control, the product is sold without warranty either express or implied and upon condition that purchaser make its own test to determine the suitability for purchaser's application. Purchaser assumes all risk of use and handling of this product. This product will be replaced if defective in manufacture or packaging or if damaged. Except for such replacement, seller is not liable for any damages caused by this product or its use. The statements and recommendations made herein are believed to be accurate. No guarantee of their accuracy is made, however.