

POLYSELECT® POWER PAC-R filtration control additive is designed to reduce the filtration rate of water-based fluids while also increasing viscosity. When added to bentonite-based fluids, POLYSELECT POWER PAC-R provides a system suitable for drilling in porous environments.

	Specifications
Appearance	White to off-white powder
pH (1% aqueous solution)	6-8

Directions for Use

Mix slowly into jet hopper and circulate throughout mud system. For normal drilling conditions, mix .5 – 1lb of POLYSELECT POWER PAC-R with 100 gallons of drilling fluid. For gravel or unconsolidated conditions, mix 1.5-3lb of POLYSELECT POWER PAC-R with 100 gallons of drilling fluid.

Packaging


POLYSELECT POWER PAC-L is sold in 25lb plastic buckets.

Applications/Functions

- Reduce formation fluid loss
- Create thin and tough filter cake
- Increase viscosity
- Reduce clay swelling and sloughing

Advantages

- Easy to mix
- Effective at low concentration
- NSF/ANSI/CAN Standard 60 certified



Bentonite Performance Minerals LLC

A Halliburton Company

3000 N. Sam Houston Pkwy E. Houston, TX 77032-3219

Phone: 281.871.7900

Email: BPMsales@halliburton.com

www.bentonite.com

Sales of BPM products and services will be in accord solely with the terms and conditions contained in the contract with BPM, its affiliates, and/or authorized distributors that is applicable to the sale. ©2021 Bentonite Performance Minerals LLC. All Rights Reserved. POLY-SELECT® is a registered trademark of Halliburton. Rev. 10/2021

