

# POLYSELECT® POWER XAN

SUSPENSION  
AGENT

**POLYSELECT® POWER XAN** suspension agent is a biopolymer designed to increase suspension characteristics of bentonite and polymer water-based drilling fluids while having minimal impact to viscosity.

	Specifications
Appearance	Free flowing beige powder
Specific Gravity	1.6
Bulk Density	45

## Directions for Use

Mix slowly into jet hopper and circulate throughout mud system. For normal drilling conditions, mix .25 – 2lb of POLYSELECT POWER XAN with 100 gallons of drilling fluid. For all polymer drilling fluids, mix 1-4lb POLYSELECT POWER XAN per 100 gallons of drilling fluid.

## Packaging

POLYSELECT POWER XAN is sold in 25lb plastic buckets.

## Applications/Functions

- Increase suspension
- Increase fluid carrying capacity
- Drilling in coarse sand/gravel

## Advantages

- Easy to mix
- Effective at low concentration
- Biodegradable
- Resistant to salt/brackish water and other contaminants
- Minimal increase to viscosity



**Bentonite Performance Minerals LLC**

**A Halliburton Company**

3000 N. Sam Houston Pkwy E. Houston, TX 77032-3219

Phone: 281.871.7900

Email: [BPMsales@halliburton.com](mailto:BPMsales@halliburton.com)

[www.bentonite.com](http://www.bentonite.com)

Sales of BPM products and services will be in accord solely with the terms and conditions contained in the contract with BPM, its affiliates, and/or authorized distributors that is applicable to the sale. ©2021 Bentonite Performance Minerals LLC. All Rights Reserved. POLY-SELECT® is a registered trademark of Halliburton. Rev. 10/2021

