

SELECTCHEM® PREMIUM WT is BPM's natural 200 mesh specialty bentonite and represents the best that BPM (and Mother Nature) has to offer. The viscosity profile from SELECTCHEM PREMIUM WT is achieved by finding the best clays and selective mining and has no additional additives. Most customers using this clay are looking for significant rheological modification including suspension, stability, and viscosity but do not want to have any synergistic effects from multiple additive treatments.

SELECTCHEM PREMIUM WT is just one product in a suite of specialty bentonite offerings from BPM under the SELECTCHEM, EXPANDA®, and VITIBEN® brands.

	Specification
Moisture, %	12.0 Max
Rheology (6% solution, Fann 600 rpm)	?
Bulk density (compacted), lbs/ft ³	73
Specific gravity	2.7
Dry screen, % minus 200	67.5 Min

Packaging

SELECTCHEM PREMIUM WT is available in 50 lb. bags and bulk bags and can ship from our Colony, WY plant.

Applications/Functions

- Organic compound stability
- Suspension agent
- Binder
- Asphalt emulsions
- Sealants
- Water proofing
- Foundry
- Coatings

Advantages

- Limited polymeric synergies
- Higher viscosity profile in fluids
- Excellent suspension & viscosity
- Stable, low separation



Bentonite Performance Minerals LLC

A Halliburton Company

3000 N. Sam Houston Pkwy E. Houston, TX 77032-3219

Phone: 281.871.7900

Email: BPMsales@halliburton.com

www.bentonite.com

Sales of BPM products and services will be in accord solely with the terms and conditions contained in the contract with BPM, its affiliates, and/or authorized distributors that is applicable to the sale. ©2021 Bentonite Performance Minerals LLC. All Rights Reserved. SELECTCHEM® is a registered trademark of Halliburton. Rev. 10/2021