

# POLYSELECT® POWER DET

WETTING  
AGENT

POLYSELECT® POWER DET wetting agent is a proprietary blend of surfactants for use in water-based drilling fluids. POLYSELECT POWER DET helps reduce the sticking tendencies of clay and shale.

	Specifications
Appearance	Clear red liquid
pH (1% solution)	8.9
Pour Point	28° F (-2.2° C)

## Directions for Use

Mix slowly into mud system away from areas that may cause aeration. To promote bit cleaning, add 2-4 pints POLYSELECT POWER DET per 100 gallons of drilling fluid. To reduce stickiness of clay and shale, add 1-4 quarts POLYSELECT POWER DET per 100 gallons drilling fluid

## Packaging

POLYSELECT POWER DET is sold in 5-gallon plastic pails.

## Applications/Functions

- Reduce stickiness of clay and shale
- Reduce bit balling

## Advantages

- Easy to mix
- Effective at low concentration
- Biodegradable



**Bentonite Performance Minerals LLC**

**A Halliburton Company**

3000 N. Sam Houston Pkwy E. Houston, TX 77032-3219

Phone: 281.871.7900

Email: [BPMsales@halliburton.com](mailto:BPMsales@halliburton.com)

[www.bentonite.com](http://www.bentonite.com)

Sales of BPM products and services will be in accord solely with the terms and conditions contained in the contract with BPM, its affiliates, and/or authorized distributors that is applicable to the sale. ©2021 Bentonite Performance Minerals LLC. All Rights Reserved. POLY-SELECT® is a registered trademark of Halliburton. Rev. 10/2021

