

BARA-KADE® PLUS

VISCOSIFIER

BARA-KADE® PLUS viscosifier is a high yield, Wyoming sodium bentonite that is commonly used in horizontal directional drilling, construction, and other applications requiring water-based drilling fluids. When mixed with water, **BARA-KADE PLUS** will increase viscosity and yield point, suspend drill cuttings, and help stabilize the bore hole.

	Specifications
Appearance	Gray to tan powder
Bulk Density (compacted), lbs/ft ³	68 to 72
pH (3% solution)	8.9

Directions for Use

Mix slowly into jet hopper and circulate throughout mud system. For normal drilling conditions, mix 15-25lb of **BARA-KADE PLUS** with 100 gallons of water. For gravel or unconsolidated conditions, mix 25-50 lb of **BARA-KADE PLUS** with 100 gallons of water.

Packaging

BARA-KADE PLUS is sold in 50lb bags on plastic wrapped pallets.

Applications/Functions

- Increase viscosity and hole cleaning
- Increase suspension
- Stabilize bore hole

Advantages

- Mixes and reaches max viscosity quickly
- NSF/ANSI/CAN Standard 60 certified



Bentonite Performance Minerals LLC

A Halliburton Company

3000 N. Sam Houston Pkwy E. Houston, TX 77032-3219

Phone: 281.871.7900

Email: BPMsales@halliburton.com

www.bentonite.com

Sales of BPM products and services will be in accord solely with the terms and conditions contained in the contract with BPM, its affiliates, and/or authorized distributors that is applicable to the sale. ©2021 Bentonite Performance Minerals LLC. All Rights Reserved. **BARA-KADE®** is a registered trademark of Halliburton. Rev. 10/2021

