



# QUIK MUD<sup>®</sup> GOLD AP

Clay/Shale Stabilizer

**Description** QUIK MUD<sup>®</sup> GOLD AP clay and shale stabilizer provides inhibition of clay and shale formations in water-based drilling fluids without substantially increasing viscosity. QUIK MUD GOLD AP clay and shale stabilizer, when added to a QUIK-GEL<sup>®</sup> or BORE-GEL<sup>®</sup> slurry, yields an inhibitive drilling fluid system while maintaining manageable and effective fluid properties.

**Applications/  
Functions**

*The use of QUIK MUD GOLD AP clay/shale stabilizer assists or promotes the following:*

- Enhanced rheological properties of a low-solids drilling fluid
- Clay and shale stabilization to prevent swelling and/or dispersion
- Borehole stability in water sensitive formations
- Minimal rotational torque and circulating pressure
- Enhanced air-foam system capabilities
- Improved core recovery in continuous wireline coring operations

**Advantages**

- NSF/ANSI Standard 60 certified
- Allows use of high concentrations to gain inhibition without producing excess viscosity
- No petroleum distillates
- Non-fermenting
- Compatible with other Baroid drilling fluid additives when added in proper sequence
- Breaks down chemically with bleach (sodium hypochlorite)

**Typical  
Properties**

- |                                    |                                   |
|------------------------------------|-----------------------------------|
| • Appearance                       | White, free-flowing coarse powder |
| • Bulk density, lb/ft <sup>3</sup> | 52                                |
| • pH ( 1% aqueous solution)        | 7.75                              |

**Recommended  
Treatment**

- Using a Venturi Mixer, or into vortex of a high-speed stirrer, add slowly and uniformly to the entire circulating system.

**See the following treatment chart or contact your local Baroid IDP Representative for assistance.**

**Recommended Treatment (continued)**

<b>Approximate Amounts of QUIK MUD® GOLD AP stabilizer Added to Water Based Fluids</b>			
<b><i>Added to fresh water (to formulate a clay-free fluid)</i></b>	<b>lb/bbl</b>	<b>lb/100 gal</b>	<b>kg/m<sup>3</sup></b>
<ul style="list-style-type: none"> <li>To stabilize water sensitive formation</li> <li>To reduce torque and lower circulating pressure</li> </ul>	0.25 – 1	0.6 – 2.4	0.7 – 2.9
<b><i>Added to QUIK-GEL® or BORE-GEL® drilling fluids</i></b>	<b>lb/bbl</b>	<b>lb/100 gal</b>	<b>kg/m<sup>3</sup></b>
<ul style="list-style-type: none"> <li>To retard reactive shale and clay and enhance lubricity</li> </ul>	0.1 – 0.3	0.25 – 0.75	0.3 – 0.9
<b><i>Added to injection fluid in air-foam applications</i></b>	<b>lb/bbl</b>	<b>lb/100 gal</b>	<b>kg/m<sup>3</sup></b>
<ul style="list-style-type: none"> <li>To reduce filtration rate and improve borehole stability</li> </ul>	0.25 – 1	0.6 – 2.4	0.7 – 2.9

- The ultimate usage concentration of QUIK MUD GOLD AP stabilizer will depend upon the quality of the make-up water used for mixing.
- Ideal make-up water has a total hardness (as calcium) less than 100 ppm (mg/L), chloride content less than 1500 ppm, chlorine content less than 50 ppm, and pH between 8.5 – 9.5.
- Reduce total hardness of make-up water by adding soda ash (sodium carbonate) at 0.5 – 1 pound per 100 gallons (0.6 – 1.2 kg/m<sup>3</sup>) of make-up water.
- QUIK MUD GOLD AP stabilizer can be chemically degraded using regular liquid household bleach (5% sodium hypochlorite). Use one gallon of liquid bleach per 100 gallons (10 liters/m<sup>3</sup>) of fluid formulated with QUIK MUD GOLD AP stabilizer.

Do not use perfumed bleach or calcium hypochlorite.

**Packaging**

QUIK MUD GOLD AP clay and shale stabilizer is packaged in 10-lb (4.5-kg) and 40-lb (18-kg) plastic pails. QUIK MUD GOLD AP stabilizer is also available in 50-lb (22.7 kg) or 55-lb (25-kg) multi-wall paper bags upon request. QUIK MUD GOLD AP stabilizer is also packaged in 15-kg drum size and 25-kg (55-lb) multi-wall paper bags in Australia/SEA.

**Availability**

QUIK MUD GOLD AP clay and shale stabilizer can be purchased through any Baroid Industrial Drilling Products Retailer. To locate the Baroid IDP retailer nearest you contact the Customer Service Department in Houston or your area IDP Sales Representative.

**Baroid Industrial Drilling Products**

**Product Service Line, Halliburton**

3000 N. Sam Houston Pkwy. E.

Houston, TX 77032

<b>Customer Service</b>	(800) 735-6075 Toll Free	(281) 871-4612
<b>Technical Service</b>	(877) 379-7412 Toll Free	(281) 871-4613