

# POLYSELECT® POWER THIN

THINNER/  
DISPERSANT

**POLYSELECT® POWER THIN** thinner and dispersant quickly acts to break up sticky clays and alter rheology of water-based drilling fluids.

|                  | Specifications       |
|------------------|----------------------|
| Appearance       | Straw colored liquid |
| Specific Gravity | 1.1-1.3              |

## Directions for Use

To reduce viscosity and gel strength, slowly add 1 pint of POLYSELECT POWER THIN to 500-1000 gallons of water-based drilling fluid and allow to circulate in mud system and homogenize. If a great reduction of viscosity and gel strength is still desired, add a small amount of POLYSELECT POWER THIN slowly to mud system until desired results are achieved.

To reduce mud rings and bit balling, add 1 pint of POLYSELECT POWER THIN to 100 gallons of drilling fluid.

## Packaging

POLYSELECT POWER THIN is sold in 5-gallon plastic pails.

## Applications/Functions

- Alter rheology
- Reduce bit balling and mud rings

## Advantages

- Effective at low concentrations
- Easy to mix
- Works quickly
- NSF/ANSI/CAN Standard 60 certified



**Bentonite Performance Minerals LLC**

**A Halliburton Company**

3000 N. Sam Houston Pkwy E. Houston, TX 77032-3219

Phone: 281.871.7900

Email: [BPMsales@halliburton.com](mailto:BPMsales@halliburton.com)

[www.bentonite.com](http://www.bentonite.com)

Sales of BPM products and services will be in accord solely with the terms and conditions contained in the contract with BPM, its affiliates, and/or authorized distributors that is applicable to the sale. ©2021 Bentonite Performance Minerals LLC. All Rights Reserved. POLY-SELECT® is a registered trademark of Halliburton. Rev. 10/2021

