

SELECTCHEM® 325

Specialty
Bentonite

SELECTCHEM® 325 is BPM's untreated blue clay that has been micro milled to 325 mesh. In fluid applications, the resulting viscosity is at a lower range. The exclusion of polymer treatment in SELECTCHEM 325 is preferred if other ingredient packages are added to the clay. SELECTCHEM 325 finds a home in various plastic and dry applications where it excels by offering low permeability, tremendous heat tolerance, and excellent release properties. Micro milling of SELECTCHEM 325 ensures unparalleled dispersion, coverage and efficient usage.

SELECTCHEM is just one product in a suite of specialty bentonite offerings from BPM under the SELECTCHEM, EXPANDA®, and VITIBEN® brands.

	Specification
pH	9.5
Moisture, %	12.0 Max
Bulk density (compacted), lbs/ft ³	65
Specific gravity	2.7
Dry screen, % minus 325	95.0 Min

Packaging

SELECTCHEM 325 is available in 50 lbs. bags and bulk bags and ships from our Colony, WY plant.

Applications/Functions

- Release agents
- Asphalt emulsions
- Sealants
- Water proofing
- Household Products
- Foundry
- Dry blending, grouts

Advantages

- Lower viscosity profile in fluids
- Excellent suspension properties
- High heat tolerance
- Full dispersion, increased coverage



Bentonite Performance Minerals LLC

A Halliburton Company

3000 N. Sam Houston Pkwy E. Houston, TX 77032-3219

Phone: 281.871.7900

Email: BPMsales@halliburton.com

www.bentonite.com

Sales of BPM products and services will be in accord solely with the terms and conditions contained in the contract with BPM, its affiliates, and/or authorized distributors that is applicable to the sale. ©2021 Bentonite Performance Minerals LLC. All Rights Reserved. SELECTCHEM® is a registered trademark of Halliburton. Rev. 10/2021

