

POLYSELECT® POWER SWELL

LOST CIRCULATION MATERIAL

POLYSELECT® POWER SWELL lost circulation material is a water swellable synthetic polymer designed to mitigate inadvertent returns and stabilize unconsolidated formations.

	Specifications
Appearance	Off-white crystals
Specific Gravity	.75
Dry Screen Analysis	96% through 5 mesh

Directions for Use

For slug treatment, add .5-1lb POLYSELECT POWER SWELL per joint. For pill treatment, add 10-20lb POLYSELECT POWER SWELL per 100 gallons of drilling fluid. Pump fluid behind slug and pill treatment to displace completely from drill rods.

Packaging

POLYSELECT POWER SWELL is sold in 20lb plastic buckets.

Applications/Functions

- Mitigate inadvertent returns
- Stabilize unconsolidated formations

Advantages

- Absorbs over 100 times its volume in water
- Small quantity yields large volume
- Easy to use
- Non-fermenting



Bentonite Performance Minerals LLC

A Halliburton Company

3000 N. Sam Houston Pkwy E. Houston, TX 77032-3219

Phone: 281.871.7900

Email: BPMSales@halliburton.com

www.bentonite.com

Sales of BPM products and services will be in accord solely with the terms and conditions contained in the contract with BPM, its affiliates, and/or authorized distributors that is applicable to the sale. ©2021 Bentonite Performance Minerals LLC. All Rights Reserved. POLY-SELECT® is a registered trademark of Halliburton. Rev. 10/2021

