

WILEY X WX GRAVITY

PROTECTIVE EYEWEAR BUILT FOR PERFORMANCE

As its name would suggest, the WX Gravity is a strong force in the Wiley X lineup, equipped with all of the features you need to maintain control in your pursuits. A slightly angled edge around the shatterproof lenses and textured detail on the rubberized temple arms are subtle and refined design elements that give the WX Gravity a modern flair. With a frame that fits comfortably on most face and head sizes, the included T-peg strap and irritant-blocking removable gasket provide extra security to the fit so your glasses stay right where they need to be.

AUTHORIZED
PROTECTIVE
EYEWEAR
LIST (APEL)
APPROVED



HIGHLIGHTS

- REMOVABLE FACIAL CAVITY™ SEAL (CH52G)
- INTERCHANGEABLE LENSES
SMOKE GREY LENS (CH52S)
CLEAR LENS (CH52C)

ALSO INCLUDES

- T-PEG STRAP (EH409-4)
- WX HARD SHELL CASE (DN750G)
- CLEANING CLOTH WITH WILEY X LOGO (A425)







PRODUCT SPECIFICATIONS

- Shatterproof Interchangeable Selenite™ Lenses
- Super-Tough Triloid Nylon Frame
- Foil™ Anti-Fog Lenses
- T-Peg Strap
- 8-Base Lenses, High-wrap Frames
- T-Shell™ Scratch Resistance
- Dual-Injection Rubber Temples and Nose Pads
- Removable Facial Cavity™ Seal
- UVA/UVB Light Blocking

CERTIFICATIONS

- ANSI Z87.1+ Impact (High-Velocity and High-Mass)
- MIL-PRF-32432A Safety Standard
- NSN / Nato List
- APEL Approved

WX GRAVITY	Protective Eyewear Built for Performance
EYEWEAR STANDARDS	<ul style="list-style-type: none"> • MIL-PRF-32432A • ANSI Z87.1+ Impact (High-Velocity and High-Mass) • APEL Approved
LENS FEATURES & TECHNOLOGY	<ul style="list-style-type: none"> • Foil™ Anti-Fog Lenses • T-Shell™ Scratch Resistance • UVA/UVB Light Blocking
WEIGHT	<ul style="list-style-type: none"> • 41.5g
BALLISTIC RATINGS	<ul style="list-style-type: none"> • MIL-SPEC SAFETY STANDARDS - Meets the Military Combat Eye Protection (MIL-PRF-32432A) standard for U.S. military standards for ballistic eye protection. For spectacles the projectile must be traveling 700-725 fps. • ANSI Z87.1+ HIGH-VELOCITY IMPACT PROTECTION - Wiley X ANSI Z87.1+ frames and lenses must withstand the impact of a .25" diameter steel ball. For spectacles the projectile must be traveling 150 fps. • ANSI Z87.1+ HIGH-MASS IMPACT PROTECTION - Wiley X ANSI Z87.1+ frames and lenses must withstand the impact of a 1.1 lb. projectile dropped from a height of 50" to ensure your eyes are protected from unexpected blunt force impacts. <div style="text-align: right; margin-top: 10px;">  <p>700-725 MIL-PRF-32432A SPECTACLE STANDARD</p>  <p>150 FPS ANSI STANDARD</p> </div>
LENS COATINGS	<ul style="list-style-type: none"> • Anti-Fog • Anti-Scratch
LENSES	<ul style="list-style-type: none"> • Shatterproof Selenite™ Lenses - Our shatterproof Selenite™ lenses are specifically designed for our high-wrap frames to ensure true spatial relationship of objects and distortion-free clarity. • Superior Lens Optics - Our lenses are ANSI Z87.1+, which means they meet or exceed national standards for safety and clarity.

APEL APPROVED Authorized Protective Eyewear List			
2 LENS PACKAGE	FRAME	LENSES	
 CH5201 <small>NSN: 4240-01-701-2897</small>	MATTE BLACK	SMOKE GREY / CLEAR	

ACCESSORIES	NSN	ITEM
DN750G	4240-01-701-3136	WX HARD SHELL CASE
CH520F	4240-01-701-3126	FRAME
CH52C	4240-01-701-2758	CLEAR REPLACEMENT LENS
CH52S	4240-01-701-2760	SMOKE GREY REPLACEMENT LENS
CH52C10	4240-01-701-2890	CLEAR REPLACEMENT LENSES (10 PCK)
CH52S10	4240-01-701-2892	SMOKE GREY REPLACEMENT LENSES (10 PCK)
CH52G	4240-01-701-8176	REPLACEMENT FACIAL CAVITY™ SEAL