

## PROCESS SERVICES | INDUSTRIAL CLEANING

# High speed flushing

Removal of deposits without the need for chemical intervention

## APPLICATIONS

- All process pipework
- Short flowlines and jumpers
- Instrument and control tubing

## FEATURES

- Suitable for non-load bearing systems
- Measured cleanliness to achieve target specifications
- Applications customized to each system

## BENEFITS

- Effective removal of large construction debris
- Minimal waste
- Safe collection of foulants
- No requirement for chemicals



## Overview

Removal of construction debris and production foulants using fluids at flowrates higher than normal operation. Achieving the necessary fluid flow rates is not always practical, particularly in large diameter piping where an alternative technique uses a combination of air and water.

The technique uses air compressors to push water through the system at the required 'flushing velocity'. Air alone is not effective at disturbing any debris, therefore water is then sprayed into the air flow to give 'mass' to the flow. Discharge is collected and allowed to separate when the liquids and any solids can be safely collected for sampling and disposal.

**For more information, contact your local Halliburton representative or visit us on the web at [www.halliburton.com](http://www.halliburton.com)**

Sales of Halliburton products and services will be in accord solely with the terms and conditions contained in the contract between Halliburton and the customer that is applicable to the sale.

H014303 09/24 © 2024 Halliburton. All Rights Reserved.

**[halliburton.com](http://halliburton.com)**

