

# SureDsolv™ P

## PARAFFIN SOLVENTS

### OVERVIEW

SureDsolv™ P is used to dissolve solid or semisolid paraffin deposits. These products improve production flow by removing paraffin wax and asphaltene from pumps, tubing, flowlines, pipelines, tanks or other processing facilities. It also contains products that are not based on benzene, ethylbenzene, toluene, or xylene (BETX).

The paraffin solvents can also be used as a preflush for scale dissolution to help increase the effectiveness of the scale removal treatment. The dissolution rate of asphaltene deposits can be enhanced nine-fold in a five-minute period with the addition of SureDsolv™ T solvent.

#### APPLICATIONS

- Effective solvents for paraffin and asphaltene removal
- Used as a preflush for oil wet scales prior to scale removal treatment
- Can be used to de-oil pipelines for change of service
- Suitable for pipeline and process applications

#### FEATURES

- High solvency power
- Higher flash point than most paraffin and asphaltene solvents
- Non-BETX products available

#### BENEFITS

- The dissolution rate of asphaltene deposits can be enhanced with the addition of SureDsolv™ T
- Solubilizes paraffin wax crystals
- Can be used in countries with strict regulations for BETX

Sales of Halliburton products and services will be in accord solely with the terms and conditions contained in the contract between Halliburton and the customer that is applicable to the sale. H014231 06/22 © 2022 Halliburton. All Rights Reserved.



For more information, contact your Halliburton representative or visit us at [halliburton.com](http://halliburton.com)

**HALLIBURTON**