

Reference / Product name: Mirka Premium Filler 3 L

Version/Revision (date): 4/02.05.2023 page 1 of 2

TECHNICAL DATA SHEET

Identification of the product and of the company/undertaking

Product identifier

9190180008 Mirka Premium Filler 3 L

Details of the supplier:

Company: Mirka Ltd

Address: Pensalavägen 210

FI-66850 Jeppo, Finland

Phone: +358 20 760 2111 National contact: sales@mirka.com

Description

The Top Premium Filler is self-leveling which makes it extremely easy to spread. It doesn't require any finishing glaze. It has excellent adhesion to many substrates including galvanized steel and aluminum. Thanks to the good sanding properties of the filler, it is a good product to reduce labor time.

Physical characteristics

Nature: Unsaturated polyester Colour: Bluish light grey 1,0 kg/l at 20°C Specific weight:

VOC: 8 g/l Mixing Application

Auxiliary products

Mirka hardener blue, 70 g.

Suitable surfaces

It may be applied on steel, electrozinc-coated, galvanised, aluminium or polyester surfaces. When maximum protection is required apply on epoxy primer. Do not apply on thermoplastic finishes and Wash Primers.

Application



2-3% **HARDENER**





5-6 MIN / 20° 20 MIN / 20° 5 MIN / max 80°





Reference / Product name: Mirka Premium Filler 3 L

Version/Revision (date): 4/02.05.2023 page 2 of 2

Remarks

Do not add more hardener than specified. Mix thoroughly. It must be isolated before applying finish coating. Polyester putties will not harden at temperatures under +5°C.

Equipment cleaning

Clean putty knifes with a cleaning thinner before the product hardens.

Safety

Follow instructions of product label. For more information check the Safety Data Sheets. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

Storage

Store the product in a ventilated place far from direct exposure to sunlight. Keep between $+5^{\circ}\text{C}$ and $+30^{\circ}\text{C}$.

Guarantee

One year in unopened original packaging.

