



Reference / Product name:
Masking Tape 90°C Orange Line

Version/Revision (date): 1/14.7.2022
page 1 of 2

TECHNICAL DATA SHEET

Identification of the product and of the company/undertaking

Product identifier


9191241801	Masking Tape 90°C Orange Line 18mm x 45m
9191242401	Masking Tape 90°C Orange Line 24mm x 45m
9191243001	Masking Tape 90°C Orange Line 30mm x 45m
9191243601	Masking Tape 90°C Orange Line 36mm x 45m
9191244801	Masking Tape 90°C Orange Line 48mm x 45m

Details of the supplier:

Company:	Mirka Ltd
Address:	Pensalavägen 210 FI-66850 Jeppo, Finland
Phone:	+358 20 760 2111
National contact:	sales@mirka.com

Description

High-grade automotive masking tape recommended for short-time automotive repair workshops and oven use. Guaranteed for 30 minutes of oven use in 90°C. Suitable for water and solvent-based paints on both metallic and plastic surfaces, with easy application on uneven surfaces thanks to excellent conformability. Absolute residue-free removal in short-time applications.





Applications

- Guaranteed spray-painting automotive oven use in 90°C for 30 minutes

Properties

- Guaranteed for 30 minutes of oven use in 90°C
- Suitable for both metallic and plastic automotive surfaces
- Suitable for water and solvent-based paints
- Easy application on uneven surfaces
- Absolute residue free removal in short time applications
- Recommended for short-term application

Nominal values

Backing

Impregnated Crepe Paper

Adhesive

Solvent-based, Natural Rubber

Tensile Strength MD

95 ± 20 (N/25mm) | ~ 21 (lb/in)
TM 5004 by Afera

Elongation at Break MD

10 ± 3 (%)
TM 5004 by Afera

Peel Adhesion on Stainless Steel

5 ± 1 (N/25mm) | ~ 18 (oz/in)
TM 5001 by Afera

Paper thickness

105 ± 15 (mic) | ~ 4,13 (mils)

Total thickness

125± 15 (mic) / ~ 4,92 (mils)

Application Range

90°C for 30 minutes
80°C for 60 minutes

