



Reference / Product name:
Mirka Plastic Putty 1 kg

Version/Revision (date): 4/02.05.2023
page 1 of 2

TECHNICAL DATA SHEET

Identification of the product and of the company/undertaking

Product identifier

9190180007 Mirka Plastic Putty 1 kg

Details of the supplier:

Company: Mirka Ltd
Address: Pensalavägen 210
FI-66850 Jeppo, Finland
Phone: +358 20 760 2111
National contact: sales@mirka.com

Description

Fast drying, easy to sand plastic putty for repairing any kind of plastic surface, including vehicle bumpers. Creamy texture and fine grain for easy application without pinholes. High flexibility and good adhesion to both flexible and rigid plastics. Easy to cover thanks to anthracite colour which matches vehicle plastics.

Physical characteristics

Nature: Unsaturated polyester
Colour: Anthracite grey
Specific weight: 1,7 kg/l at 20°C
Voc: 41 g/l Mixing Application

Auxiliary products

Mirka hardener red, 25 g.

Suitable surfaces

It may be applied on flexible bodywork plastics such as PP/EPDM, ABS, PA, PUR, PC and rigid plastics such as POLYESTER (SMC and UP-GFK). Do not apply on thermoplastic finishes and wash primers.

Application



2-3 %
HARDENER



4-5 MIN / 20°



25 MIN / 20°





Reference / Product name:
Mirka Plastic Putty 1 kg

Version/Revision (date): 4/02.05.2023
page 2 of 2

Remarks

Do not add more hardener than specified. Mix thoroughly.
It must be isolated before applying finish coating.
Polyester putties will not harden at temperatures under +5°C.

Equipment cleaning

Clean putty knives with a cleaning thinner before the product hardens.

Safety

Follow instructions of product label. For more information check the Safety Data Sheets.
Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

Storage

Store the product in a ventilated place far from direct exposure to sunlight.
Keep between +5°C and +30°C.

Guarantee

In unopened original packaging, one year from manufacturing date.

