



Reference / Product name:
Mirka Soft Light Putty 1,2 kg

Version/Revision (date): 4/02.05.2023
page 1 of 2

TECHNICAL DATA SHEET

Identification of the product and of the company/undertaking

Product identifier

9190180005 Mirka Soft Light Putty 1,2 kg

Details of the supplier:

Company: Mirka Ltd
Address: Pensalavägen 210
FI-66850 Jeppo, Finland
Phone: +358 20 760 2111
National contact: sales@mirka.com

Description

Multi-purpose and versatile product with great filling properties and excellent adhesion. Easy to mix and apply, easy to sand. Can be used as a finishing putty without pinholing, suitable for sanding with P100-120 depending on the repaired area. Suits both small and large applications.

Physical characteristics

Nature: Unsaturated polyester
Colour: Beige
Specific weight: 1,2 kg/l at 20°C
VOC: 25 g/l Mixing Application

Auxiliary products

Mirka hardener red, 35 g.

Suitable surfaces

It may be applied on steel, aluminium, galvanised, polyester surfaces and OEM Paint.
When maximum protection is required apply on epoxy primer.
Do not apply on thermoplastic finishes and Wash Primers.

Application



2-3 %
HARDENER



4-5 MIN / 20°



25 MIN / 20°



5 MIN / max 80°





Reference / Product name:
Mirka Soft Light Putty 1,2 kg

Version/Revision (date): 4/02.05.2023
page 2 of 2

Remarks

Do not add more hardener than specified. Mix thoroughly.
It must be isolated before applying finish coating.
Polyester putties will not harden at temperatures under +5°C.

Equipment cleaning

Clean putty knives with a cleaning thinner before the product hardens.

Safety

Follow instructions of product label. For more information check the Safety Data Sheets.
Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

Storage

Store the product in a ventilated place far from direct exposure to sunlight.
Keep between +5°C and +30°C.

Guarantee

One year in unopened original packaging.

