

**TECHNICAL DATA SHEET****Identification of the product and of the company/undertaking****Product identifier**

9190110012	Masking Film Standard, 4m x 150m
9190110013	Masking Film Standard, 5,3m x 150m

**Details of the supplier:**

Company:	Mirka Ltd
Address:	Pensalavägen 210 FI-66850 Jeppo, Finland
Phone:	+358 20 760 2111
National contact:	sales@mirka.com

**Product Description**

- 9 micron ( $\mu$ ) thick masking film
- High Density Polyethylene Film (PE-HD)
- Electrostatic and treated to ensure fast, easy and complete vehicle masking
- Excellent paint overspray adhesion and no paint flaking

**Hazards Identification**

No specific danger concerns and no hazard if used for intended application.  
This material is not classified as dangerous according to EU directives.

**First-Aid Measures**

No specific measures need to be taken.

**Firefighting measures**

Material cannot burn unless preheat and requires a continuous flame source to ignite.  
Extinguishing Agents: Water spray, chemical powder, carbonic dioxide.

**Storage Conditions**

Store under dry conditions and well-ventilated position.  
Do not store near sources of heat and keep away from direct sunlight.  
Let the material stored in its original packaging and protected against moisture and dust.

**Physical and chemical properties**

Physical state: Solid (film)  
Density: 0,95 gr/cm<sup>3</sup>

**Toxicological information**

No irritant effects. Not sensitising effect known.  
Not Toxic and/ or harmful effects are expected in case of skin contact.



**Ecological information:**

- This material is 100% recyclable
- The material is not considered hazardous waste; scrap materials may be disposed of at approved landfills or preferably by incineration in accordance with existing international, EU Community, national and local regulations
- All disposal methods must be in compliance with the EU framework directive 91/156/EEC.

**Transport information**

According to national and international guidelines, which regulate the road-, rail-, air-, and sea transport, this product is classified as not dangerous.

**Shelf Life**

7-10 months

**Custom Tariff number**

3920-10

