



Reference / Product name:
Mirka Pro Filler 3 L

Version/Revision (date): 4/02.05.2023
page 1 of 2

TECHNICAL DATA SHEET

Identification of the product and of the company/undertaking

Product identifier

9190180009 Mirka Pro Filler 3 L

Details of the supplier:

Company: Mirka Ltd
Address: Pensalavägen 210
FI-66850 Jeppo, Finland
Phone: +358 20 760 2111
National contact: sales@mirka.com

Description

The Pro Filler is intended for those repairs where the filling capacity is very important. Multi-purpose for small or large applications, adhesion to any type of metal surface. Easy to apply and easy to sand. For the perfect result, finish with the Premium filler for an excellent finish.

Physical characteristics

Nature: Unsaturated polyester
Color: Grey
Specific weight: 1,0 kg/l at 20°C
VOC: 16 g/l Mixing Application

Auxiliary products

Mirka hardener red, 70 g.

Suitable surfaces

It may be applied on steel, electrozinc-coated, galvanised, aluminium or polyester surfaces.
When maximum protection is required apply on epoxy primer.
Do not apply on thermoplastic finishes and Wash Primers.

Application



2-3 %
HARDENER



4-5 MIN / 20°



20 MIN / 20°



5 MIN / max 80°





Reference / Product name:
Mirka Pro Filler 3 L

Version/Revision (date): 4/02.05.2023
page 2 of 2

Remarks

Do not add more hardener than specified. Mix thoroughly.
It must be isolated before applying finish coating.
Polyester putties will not harden at temperatures under +5°C.

Equipment cleaning

Clean putty knives with a cleaning thinner before the product hardens.

Safety

Follow instructions of product label. For more information check the Safety Data Sheets.
Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

Storage

Store the product in a ventilated place far from direct exposure to sunlight.
Keep between +5°C and +30°C.

Guarantee

In unopened original packaging, one year from manufacturing date

