



## TECHNICAL INFORMATION

|                         |                          |
|-------------------------|--------------------------|
| Dimensions              | 630w x 735d x 1470-1960h |
| Rack Dimension          | 500 x 500                |
| Clear Entry Height      | 440                      |
| Rinse Water Consumption | 3.25L Per Cycle          |

## WATER CONNECTIONS

|                   |                 |
|-------------------|-----------------|
| Connection Point  | 3/4 inch (19mm) |
| Inlet Temperature | 60c Max         |
| Flow Rate         | 11 L/Min        |
| Flow Pressure     | 0.5 bar         |

## ELECTRICAL

|                    |                                   |
|--------------------|-----------------------------------|
| 3 Phase (Standard) | 415v 3P 50Hz - 20amp (TCL 9.32Kw) |
|--------------------|-----------------------------------|

## GENERAL DATA

|                      |                        |
|----------------------|------------------------|
| Weight (Net/Gross)   | 137Kg / 185Kg          |
| Tank Capacity        | 39L                    |
| Noise Emission       | 70dB(A)                |
| Cycle Times          | 1.5 / 3.0 / 5.0 Minute |
| Theoretical Capacity | 720 plates per hour    |

## STANDARD INCLUSIONS

|                                      |
|--------------------------------------|
| 1x 3 Phase Lead                      |
| 1x 1M Flexible Water Connection Hose |
| 1x 1M Flexible Waste Hose            |
| 1x 500 x 500 Flat Cup Basket         |
| 1x 500 x 500 Peg Plate Basket        |
| 1x 8 Compartment Cutlery Basket      |

## STANDARD FEATURES

- LCD control with digital temperature display
- Drain pump
- Rinse pump
- Integrated chemical pumps
- Dual filtration
- 'Air gap' back flow prevention
- Anti-block wash arms, lightweight and easy to remove for cleaning
- Made in UK
- Watermark approved
- Suitable for straight and corner operation