

DETONATOR ASSEMBLY, A-140S, DIGITAL FIRE, VEL GEN II

Part No.: 102947849

CE Certificate No.: N/A


DOT EX No.: EX2019082403

PROPER SHIPPING NAME

UN0255, DETONATORS, ELECTRIC,

1.4B

Technical Drawing



Technical Information

APPLICATION:

Velocity detonator Gen II for oilfield use.

RF-SAFE:

RF-Safe for all oil field applications (Franklin Applied Physics report, December 2017)

EXPLOSIVE COMPONENTS:

Ignition charge: proprietary, 0.170 g

Base charge: RDX, 0.325 g

Packing Information

Quantity per box: 20 pieces

ROTATED ISO VIEW

Gross weight per box: 3.0 kg (6.6 lbs.) Net weight per box: 2.45 kg (5.4 lbs.)

NEC per box: 0.0098 kg

Box dim: 33.8 X 27.5 X 18.1 cm

13.3 X 10.8 X 7.1 in

Package type: Detonator is sealed in foil bag with desiccant, then placed into a white reverse tuck carton. The inner packaging is placed upright into a fiberboard box. Up to 20 of the inner packaging cartons can be packaged inside fibreboard box.

Product Designation: 4-2 rev XP

TEMPERATURE LIMITS:

325 F / 162 C 1 h 260 F / 125 C 24 h 225 F / 107 C 100 h

SHELF LIFE:

5 years when stored unopened in original packaging. Storage temperature: 0 C / 32 F min 54 C / 130 F max

DISPOSAL:

Dispose of product not suitable for oilfield use according to applicable laws and regulations.

Tel.: +1 817.761.2000

D01818567 Rev. A