

Wireline Setting Tools

RELIABLE SETTING OF SUBSURFACE DEVICES

OVERVIEW

Halliburton offers a comprehensive family of setting tools that provide industry-trusted reliability for deployment and setting of conventional wellbore devices, including plugs, packers, and cement retainers in both vertical and horizontal applications.

With a wide range of stroke lengths and setting forces available, Halliburton can provide the ideal setting-tool solution for your specific application.

Firing heads supplied with the setting tools accept a standard GO-style igniter, such as the Halliburton RF-Safe Igniter. Firing heads that accept the Halliburton RED® Igniter, an RF-Safe/Stray Voltage-Safe igniter, are also available.

These setting tools are not dependent on a specific oil level to achieve full stroke, making them less susceptible to wellbore temperatures, and their downhole self-bleeding action enables improved safety during operation.

BENEFITS

- » Provides reliable setting of subsurface devices
- » Ideal for vertical and horizontal applications
- » Less susceptible to downhole temperature
- » Pressure-Balanced System prevents presetting devices

FEATURES

- » High-pressure-rated tools available
- » Uses RED igniters for increased operational safety and efficiency
- » Self-bleeding action downhole for improved safety
- » Oil level not critical for device setting



Shorty Setting Tool Specifications

Description	PN	Diameter	RIH Length	Stroke	Stroked Length	Force	Pressure Rating
1 ¹ / ₁₆ -in. Long Stroke	101974677	1.69 in. (42.93 mm)	34.88 in. (88.60 cm)	10.07 in. (25.60 cm)	85.22 in. (216.46 cm)	15,000 lb (66.72 kn)	20,000 psi (137.90 Mpa)
2 ¹ / ₈ -in. Multistage	101971445	2.13 in. (54.10 mm)	90.06 in. (228.75 cm)	9.675 in. (24.57 cm)	100.56 in. (255.42 cm)	25,000 lb (111.20 kn)	20,000 psi (137.90 Mpa)
1 ¹ / ₁₆ -in. Shorty	101924801	1.69 in. (42.93 mm)	34.88 in. (88.60 cm)	3.36 in. (8.53 cm)	38.88 in. (98.76 cm)	15,000 lb (66.72 kn)	20,000 psi (137.90 Mpa)
2 ¹ / ₂ -in. Shorty	101965920	2.50 in. (63.50 mm)	57.56 in. (146.20 cm)	9.72 in. (24.68 cm)	68.06 in. (172.87 cm)	35,000 lb (155.69 kn)	17,000 psi (117.21 Mpa)
2 ³ / ₄ -in. Shorty*	101916335	2.75 in. (69.6 mm)	57.56 in. (146.20 cm)	9.72 in. (24.68 cm)	68.06 in. (172.87 cm)	35,000 lb. (115.69 kn)	25,000 psi (172.34 Mpa)
3 ¹ / ₂ -in. Shorty ¹	102112757	3.50 in. (88.90 mm)	51.70 in. (131.30 cm)	8.75 in. (22.23 cm)	61.32 in. (155.75 cm)	57,500 lb (255.77 kn)	15,000 psi (103.42 Mpa)
3 ¹ / ₂ -in. Shorty ²	101974666	3.50 in. (88.90 mm)	53.19 in. (135.10 cm)	8.75 in. (22.23 cm)	62.81 in. (157.54 cm)	57,500 lb (255.77 kn)	20,000 psi (137.90 Mpa)

¹ GO Style Quick Change

² SIE Style Quick Change

² Note: Requires Contact Block 100014459 and Contact Plug 101320910

* 2³/₄-in. Shorty delivered with lower connections cloning a Baker E-4 #10 WST

RED® Firing Head Adapters

Setting Tool	RED® Igniter	RED® Firing Head Adapter	Firing Head
1 ¹ / ₁₆ -in. Long Stroke	102351326	101293376	100013383
2 ¹ / ₈ -in. Multistage	102351326	101294740	100013383
1 ¹ / ₁₆ -in. Shorty	102351326	102011481	100013383
2 ¹ / ₂ -in. Shorty	102351326	101293430	100013383
2 ³ / ₄ -in. Shorty	102351326	101944433	100157532
3 ¹ / ₂ -in. Shorty ²	102351326	101741458	100014458

Note: All Setting tools come with firing head adapters that accept resistorized GO-style Igniter 100004220.

Not all available firing heads and adapters listed.

For more information, contact your local Halliburton representative or visit us on the web at www.halliburton.com

Sales of Halliburton products and services will be in accord solely with the terms and conditions contained in the contract between Halliburton and the customer that is applicable to the sale.

H01886 1/18 © 2018 Halliburton. All Rights Reserved.