DETONATOR ASSEMBLY, A-140S,CONT FIRE,VEL GEN II	
Part No.: 102895443	PROPER SHIPPING NAME
CE Certificate No.: N/A	
DOT EX No.: EX2019082403	UN0255, DETONATORS, ELECTRIC, 1.4B
Technical Drawing	Technical Information
	APPLICATION: Velocity detonator Gen II for oilfield use.
ASSEMBLED VIEW	RF-SAFE: RF-Safe for all oil field applications (Franklin Applied Physics report, December 2017)
ROTATED ISO VIEW	EXPLOSIVE COMPONENTS: A-140S DETONATOR: 0.53 g
	TEMPERATURE LIMITS:
Packing Information	325 F / 162 C 1 h 260 F / 125 C 24 h
Quantity per box: 20 pieces	225 F / 107 C 100 h
Gross weight per box: 1.32 kg (2.91 lbs.) Net weight per box: 0.76 kg (1.68 lbs.)	SHELF LIFE:
NEC per box: 0.0106 kg	5 years when stored unopened in original packaging. Storage temperature: 0 C / 32 F min 54 C / 130 F max
Box dim: 20.3 X 16.3 X 11.7 cm 8 X 6.4 X 4.6 inch	
Package type: Detonator is sealed in antistatic bag with desiccant, then placed into a white reverse tuck carton. The inner packaging is placed upright into a fiberboard box. Up to 20 of the inner packaging cartons can be packaged inside fiberboard box.	DISPOSAL: Dispose of product not suitable for oilfield use according to applicable laws and regulations.
Product Designation: 4-2 rev XP	D01818296 Rev. D
Jet Research Center, a division of Halliburton Energy Services, I	

JRC