

FEATURES AND BENEFITS

Breech Lock running tool

- Multiple applications
- Rotational and reciprocation (deployment and cementing)
- Up to five times the compressive load capacity of a standard VersaFlex ELH hanger and tool system

Breech Lock hanger

- Gas-tight seal
- Redundant sealing areas
- Immediate liner-top integrity test
- Withstands high-circulating rates
 - No external moving parts
 - Sets in any casing hardness

APPLICATIONS

- Cemented liners
- Unconventional reservoirs utilizing frac sleeves and isolation devices
- Multilateral liners
- Drop-off liners

CAPEX

- Reduces rig time
- Eliminates remediation


COMPLETION SOLUTIONS | LINER HANGERS

VersaFlex® Breech Lock system

Reach total depth in extended-reach and long horizontal completions

Overview

When liner strings have to travel through tortuous well paths, including sudden elevation drops or azimuthal swings, or in short radius horizontal wells, extreme compressive force is often required for liner deployment. The VersaFlex® Breech Lock system offers an unparalleled unique design to increase the compressive load capability of the running tool. This allows operators to reach total well depth, particularly in highly deviated or long openhole horizontal wells and extended-reach drilling (ERD) wells. The system also addresses concerns associated with deployment of liner strings made up of multiple stimulation components. Excessive loads on the liner hanger are eliminated and are directed to the liner threads instead to minimize risks during liner hanger deployment and setting operations.



How it works

The VersaFlex® Breech Lock system utilizes the same proven running tool design as its parent VersaFlex system and with the same unmatched reliable set-and-forget redundant seals. The Breech Lock running tool works in tandem with the VersaFlex expandable liner hanger (ELH) to support liner deployment with rotational capabilities. As an integral hanger/packer system with no moving parts, this helps eliminate costly tool failures associated with conventional liner hangers.

The VersaFlex Breech Lock system provides a competent gas-tight seal—without cement—on setting at high angles as compressive loads are not required to activate, set, or seal the liner-top packer. Prior to release, its rotation and reciprocation capability allows for the best possible cement placement and bond when required.

VersaFlex® Breech Lock system specifications

BREECH LOCK RUNNING TOOL	SET TYPE	BODY PROFILE	LINER SIZE	HANGER SIZE
			IN.	IN.
Standard Breech Lock (Pile Driver)	Ball	VersaFlex Standard	4 1/2; 5	7
		VersaFlex Standard	5 1/2	7
	Ball	VersaFlex Standard	4 1/2; 5	7
		VersaStim®	4 1/2; 5	7
Adjustable Pressure Set Breech Lock	Ball	SelectFlex®	4 1/2; 5	7
		VersaFlex Standard / High-Torque	7; 7 5/8	9 5/8; 9 7/8
	Flapper or Ball	VersaFlex Drop-off	7; 7 5/8	9 5/8; 9 7/8
		VersaStim	7; 7 5/8	9 5/8; 9 7/8

For more information, contact your local Halliburton representative or visit us on the web at www.halliburton.com

Sales of Halliburton products and services will be in accord solely with the terms and conditions contained in the contract between Halliburton and the customer that is applicable to the sale.

H08608 11/24 © 2024 Halliburton. All Rights Reserved.

halliburton.com

HALLIBURTON