

UNCONVENTIONAL COMPLETIONS | DRILLABLE TOOLS

# Fas Drill<sup>®</sup> bridge plug

Field-proven reliable well control

## FEATURES AND BENEFITS

- Consists of composites and a packer set, giving it minimal ferrous metal content
- Isolates a lower zone during squeeze cementing operations on land-based or offshore rigs, in vertical or deviated wells
- Functions as a bridge plug in multizone stimulation treatments
- Saves rig time and reduces casing damage caused by long drillout processes
- Drills out with conventional tricone, PDC\*, or with junk-mill bits

## Overview

The Fas Drill<sup>®</sup> bridge plug, manufactured from composite materials, functions similarly to a conventional drillable bridge plug. It is ideal for situations requiring temporary abandonment or where minimal weight is available to remove a conventional metal bridge plug. Halliburton drillable bridge plugs, are top drilling, meaning the tool will allow for equalization before the top anchoring slips are drilled, resulting in reliable well control.



HAL122851

Fas Drill<sup>®</sup> bridge plug

**Fas Drill® bridge plug**

CASING SIZE	MAX CASING ID	MIN CASING ID	MAX TOOL OD	TOOL LENGTH	PRESSURE RATING
IN. (CM)	IN. (CM)	IN. (CM)	IN. (CM)	IN. (CM)	PSI (MPA)
4 ½ HW	3.826 (9.71)	3.640 (9.24)	3.44 (8.74)	28.91 (73.43)	10,000 (68.95)
4 ½	4.090 (10.39)	3.920 (9.96)	3.66 (9.30)	29.70 (75.44)	10,000 (68.95)
5 HW	4.276 (10.86)	4.126 (10.48)	3.85 (9.78)	26.34 (66.90)	10,000 (68.95)
5	4.560 (11.58)	4.276 (10.86)	3.97 (10.08)	31.73 (80.59)	10,000 (68.95)
5 1/2	4.778 (12.14)	4.376 (11.11)	4.15 (10.54)	33.49 (85.06)	10,000 (68.95)
5 1/2	4.950 (12.57)	4.670 (11.86)	4.37 (11.10)	33.98 (86.31)	10,000 (68.95)
6	5.240 (13.31)	5.007 (12.72)	4.70 (11.94)	26.45 (67.18)	8,000 (55.16)
7 HW	6.184 (15.70)	5.920 (15.04)	5.50 (13.97)	35.04 (89.00)	8,000 (55.16)
7	6.366 (16.18)	6.184 (15.70)	5.80 (14.73)	35.57 (90.35)	10,000 (68.95)
7 5/8	7.125 (18.10)	6.501 (16.51)	6.12 (15.54)	35.09 (89.13)	5,000 (34.47)
9 5/8	9.063 (23.01)	8.157 (20.73)	7.75 (19.69)	46.60 (118.36)	5,000 (34.47)
10 3/4	9.950 (25.27)	9.560 (24.28)	9.00 (22.86)	46.79 (118.85)	5,000 (34.47)
13 3/8	12.715 (32.31)	12.280 (31.19)	11.68 (29.67)	46.59 (118.34)	5,000 (34.47)

Note: Other tool sizes may be available. These ratings are guidelines only. For more information, contact your local Halliburton representative.

For more information, contact your local Halliburton representative or visit us on the web at [www.halliburton.com](http://www.halliburton.com)

Sales of Halliburton products and services will be in accord solely with the terms and conditions contained in the contract between Halliburton and the customer that is applicable to the sale.

H06160 11/24 © 2024 Halliburton. All Rights Reserved.