

EZ Drill® SVB Squeeze Packers

**OFFER ENHANCED RELIABILITY, REDUCED RIG TIME,
AND QUICK DRILL OUT**

OVERVIEW

EZ Drill® SVB (sliding valve brass) squeeze packers can be used for applications, such as wellbore isolation, remedial cementing, and plug and abandonment. Equipped with a rugged brass mandrel, the packer can absorb greater tensile and impact loads. Additionally, the EZ Drill SVB squeeze packer can control flow and differential pressure in either direction by workstring manipulation of the sliding valve inside the tool. Using a conversion kit, EZ Drill SVB squeeze packers can be altered to create a top-drilling bridge plug capable of holding differential pressure in either direction.

FEATURES

- » Mechanically or hydraulically set on jointed pipe, coiled tubing, electric wireline or slickline using the Halliburton DPU® downhole power unit
- » Sets in a wide range of casing sizes and grades
- » Effective setting and sealing in elevated temperatures and pressures
- » Available with API 11D1 designation.

BENEFITS

- » Equipped with a brass mandrel that absorbs greater tensile and impact loads as compared to cast iron mandrel tools.
- » Tool OD held to a minimum, allowing more clearance between the tool and casing for faster run-in



EZ Drill® SVB Squeeze Packer Specifications

Casing Size in. (mm)	Maximum Casing ID in. (mm)	Minimum Casing ID in. (mm)	Maximum Tool OD in. (mm)	Rated Pressure psi (MPa)	API 11D1 Qualified
3 1/2 (88.9)	3.240 (82.3)	2.890 (73.4)	2.69 (68.3)	10,000 (69.0)	
4 (101.6)	3.640 (92.5)	3.320 (84.3)	3.12 (79.2)	10,000 (69.0)	
4 1/2 (114.3)	3.920 (99.6)	3.826 (97.2)	3.58 (90.9)	10,000 (69.0)	
5 (127.0)	4.560 (115.8)	4.276 (108.6)	3.97 (100.8)	10,000 (69.0)	X
5 1/2 (139.7)	5.040 (128.0)	4.670 (118.6)	4.37 (111.0)	10,000 (69.0)	X
6 (152.4)	5.590 (142.0)	5.220 (132.6)	4.87 (123.7)	10,000 (69.0)	
6 5/8 (168.3)	5.900 (149.9)	5.670 (144.0)	5.32 (135.1)	10,000 (69.0)	
7 (177.8)	6.460 (164.1)	5.900 (149.9)	5.50 (139.7)	10,000 (69.0)	X
7 5/8 (193.7)	7.125 (181.0)	6.500 (165.1)	6.12 (155.4)	10,000 (69.0)	X
8 5/8 (219.1)	7.830 (198.9)	7.310 (185.7)	6.88 (174.8)	10,000 (69.0)	
8 5/8 (219.1)	8.130 (206.5)	7.450 (189.2)	7.00 (177.8)	10,000 (69.0)	
9 5/8 (244.5)	9.063 (230.2)	8.157 (207.2)	7.74 (196.6)	7,500 (51.7)	X
10 3/4 (273.1)	9.500 (241.3)	9.156 (232.6)	8.69 (220.7)	7,500 (51.7)	X
10 3/4 (273.1)	10.192 (258.9)	9.560 (242.8)	9.00 (228.6)	7,500 (51.7)	X
11 3/4 (298.5)	10.406 (264.3)	10.282 (261.2)	9.73 (247.1)	7,500 (51.7)	
11 3/4 (298.5)	11.084 (281.5)	10.438 (265.1)	9.87 (250.7)	7,500 (51.7)	
13 3/8 (339.7)	12.281 (311.9)	11.907 (302.4)	11.31 (287.3)	5,000 (34.5)	
13 3/8 (339.7)	12.715 (323.0)	12.281 (311.9)	11.68 (296.7)	5,000 (34.5)	X
16 (406.4)	15.250 (387.4)	14.688 (373.1)	13.96 (354.6)	2,500 (17.2)	X
18 5/8 (473.1)	18.000 (457.2)	17.439 (443.0)	16.80 (426.7)	2,500 (17.2)	
20 (508.0)	19.124 (485.7)	17.938 (455.6)	17.24 (437.9)	2,500 (17.2)	

These ratings are guidelines only. For more information, contact your local Halliburton representative.

For more information, contact your local Halliburton representative
or visit us on the web at www.halliburton.com

Sales of Halliburton products and services will be in accord solely with the terms and conditions contained in the contract between Halliburton and the customer that is applicable to the sale.

H013825 02/21 © 2021 Halliburton. All Rights Reserved.