

## WELL COMPLETIONS | SUBSURFACE FLOW CONTROLS

## FEATURES

- Robust and simple uni-body style plug with one moving part (key expander) eliminates internal leak paths
- V0-qualified high-pressure/high-temperature (HP/HT) non-elastomer seal stack
- 3 x 45° loading surfaces on key above and below, maximizing key bearing area
- Up to 25,000-psi pressure rating at 450°F
- Metal-to-metal (MTM) shear plug for equalizing in pump-through type
- Holddown feature locks plug in the set position

## BENEFITS

- Bubble-tight seal performance at ultra-high pressures and temperatures
- Key/nipple profile configuration provides ultra-high-pressure capability while minimizing component stress levels
- All seals are inert to all known well fluids and are unaffected by rapid gas decompression
- Pump-through plug type allows for well kill while installed in the nipple profile
- Pre-install capabilities of the positive-type plug in the completion helps eliminate the need to run wireline to set the plug body
- Running tool does not release until lock is correctly and fully set
- Pulling tool will not engage unless pressure equalizes across the plug

## SRH plug

Positive plug and nipple system for high pressure/high temperature (HP/HT)

## Overview

SRH high-pressure plugs are designed for use in extreme temperature and pressure environments and use the top no-go location and is designed such that pressure from above and below is held by key/nipple engagement. Special non-elastomer V-packing stacks are gas-tight qualified up to 25,000 psi at 450°F.

## Applications

SRH plugs are available in, pump-through and positive type. The pump-through type incorporates a poppet that has a MTM seal backed up by an HP/HT non-elastomer V-packing stack. A MTM knockout plug is provided for equalization. A test prong can be run to convert the pump-through plug into a positive plug for testing from above. The two-trip prong-type plug is a positive plug with no pump-through feature. The packing on the prong uses the same type of HP/HT V-packing stacks as used on the plug body. The prong is pressure balanced for easy removal under high-pressure differential to allow for equalizing before retrieving the plug.



HCT1768-001

SRH Positive Plug



HCT1788-002



HCT1788-003

SRH pump-through plug

SRH pump-through plug with positive prong installed

**For more information, contact your local Halliburton representative or visit us on the web at [www.halliburton.com](http://www.halliburton.com)**

Sales of Halliburton products and services will be in accord solely with the terms and conditions contained in the contract between Halliburton and the customer that is applicable to the sale.

H09827 11/24 © 2024 Halliburton. All Rights Reserved.

**halliburton.com**

**HALLIBURTON**