

## Camshelving® Premium Series

### Stationary Starter & Add-on Units 4 or 5 Vented Shelves

HEIGHT	DEPTHS	LENGTHS	
1	3	8	
1630 mm	460 mm	610 mm	1220 mm
	540	765	1375
	610	915	1525
		1070	1830

- **Starter Units include:**  
2 factory assembled post kits and 8 or 10 traverses and shelf plates.
  - **Add-On Units include:**  
1 factory assembled post kit and 8 or 10 traverses and shelf plates.
- Units ship complete in 1 box.

#### Features & Benefits

- Modular, hygienic, stable and durable, Camshelving Premium Series Shelving is perfect for use in high-volume operations with constant loading of heavy products and frequent daily deliveries.
- Withstands storage temperatures from -38°C to 88°C. Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Impervious to moisture, chemicals, salt, food acids, and humidity.
- Posts and traverses have a steel core and smooth polypropylene exterior for superior strength and durability.
- Removable polypropylene shelf plates have permanent, molded-in Camguard, an antimicrobial technology that inhibits the growth of mold, fungus and bacteria.
- Fast assembly. Shelves connect and can be adjusted easily on the dovetails molded into posts every 10,2 cm.
- Sturdy reinforced nylon foot adjusts easily to level units.
- Shelving units interconnect in straight lines with shared posts. Weight bearing is uncompromised and space is maximized. Possible configuration in "L", "U", "T" or "Cross" layouts using corner connectors.
- Posts, traverses and shelf plates wipe clean or can be run through a dishwasher.
- Lifetime warranty against rust and corrosion.
- Available in 1 color – Speckled Gray (480).

Project \_\_\_\_\_

Item No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_



Stationary Starter Unit



Stationary Add-On Unit

### Premium Series Weight Bearing Capacity

Weight must be evenly distributed across the entire shelf.

		UNIT LENGTH 610 – 1220 MM	UNIT LENGTH 1375 – 1830 MM
<b>SINGLE UNIT</b>	Unit only	910 kg	910 kg
	Shelf only	365	275
	Unit with dunnage stand*	1110	1045
	Bottom shelf with dunnage stand*	545	410
<b>CORNER UNIT**</b> With 2 Dunnage Stands required	Unit only	820	—
	Shelf only	185	—
	Bottom shelf with dunnage stands*	275	—
<b>MOBILE UNIT</b>	Unit only***	340	—

\* Dunnage Stands add stability and increase weight bearing capacity on bottom shelf only. Add to any shelf length. Highly recommended for Starter Units 1375 mm and longer, all Corner Units, U-Shape Units and units specified for heavier loads.

\*\* Corner connectors are for use only with shelves 610 - 1220 mm long.

\*\*\* Due to the weight bearing capacity of casters, maximum weight load on an entire Mobile Unit is 340 kg.

#### Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Security Cages, Single Shelf Sheet Pan/Tray Rack, Shelf Rails, Divider Bars, High Density Track and Extension Kits are not NSF Listed.

# Camshelving® Premium Series

## Stationary Starter & Add-on Units 4 or 5 Vented Shelves

Project \_\_\_\_\_

Item No. \_\_\_\_\_

Model No. \_\_\_\_\_


Quantity \_\_\_\_\_

### V4


**1630**  
mm  
HEIGHT

### 4-Shelf Vented Units

Starter



Add-On



**460**  
mm  
DEPTH

LENGTH	CODE
610 mm	CPU182464S4
765	CPU183064S4
915	CPU183664S4
1070	CPU184264S4
1220	CPU184864S4
1375	CPU185464S4
1525	CPU186064S4
1830	CPU187264S4PKG

LENGTH	CODE
565 mm	CPA182464V4
718	CPA183064V4
870	CPA183664V4
1023	CPA184264V4
1175	CPA184864V4
1328	CPA185464V4
1480	CPA186064V4
1778	CPA187264V4PKG

**540**  
mm  
DEPTH

610 mm	CPU212464V4
765	CPU213064V4
915	CPU213664V4
1070	CPU214264V4
1220	CPU214864V4
1375	CPU215464V4
1525	CPU216064V4
1830	CPU217264V4PKG

565 mm	CPA212464V4
718	CPA213064V4
870	CPA213664V4
1023	CPA214264V4
1175	CPA214864V4
1328	CPA215464V4
1480	CPA216064V4
1778	CPA217264V4PKG

**610**  
mm  
DEPTH

610 mm	CPU242464V4
765	CPU243064V4
915	CPU243664V4
1070	CPU244264V4
1220	CPU244864V4
1375	CPU245464V4
1525	CPU246064V4
1830	CPU247264V4PKG

565 mm	CPA242464V4
718	CPA243064V4
870	CPA243664V4
1023	CPA244264V4
1175	CPA244864V4
1328	CPA245464V4
1480	CPA246064V4
1778	CPA247264V4PKG


Color: Speckled Gray (480).

Due to the unit weight, PKG units ship in separate cartons. Post kits require assembly.


### V5

### 5-Shelf Vented Units

Starter



Add-On



LENGTH	CODE
610 mm	CPU182464V5
765	CPU183064V5
915	CPU183664V5
1070	CPU184264V5
1220	CPU184864V5
1375	CPU185464V5
1525	CPU186064V5
1830	CPU187264V5PKG

LENGTH	CODE
565 mm	CPA182464V5
718	CPA183064V5
870	CPA183664V5
1023	CPA184264V5
1175	CPA184864V5
1328	CPA185464V5
1480	CPA186064V5
1778	CPA187264V5PKG

610 mm	CPU212464V5
765	CPU213064V5
915	CPU213664V5
1070	CPU214264V5
1220	CPU214864V5
1375	CPU215464V5
1525	CPU216064V5
1830	CPU217264V5PKG

565 mm	CPA212464V5
718	CPA213064V5
870	CPA213664V5
1023	CPA214264V5
1175	CPA214864V5
1328	CPA215464V5
1480	CPA216064V5
1778	CPA217264V5PKG

610 mm	CPU242464V5
765	CPU243064V5
915	CPU243664V5
1070	CPU244264V5
1220	CPU244864V5
1375	CPU245464V5
1525	CPU246064V5
1830	CPU247264V5PKG

565 mm	CPA242464V5
718	CPA243064V5
870	CPA243664V5
1023	CPA244264V5
1175	CPA244864V5
1328	CPA245464V5
1480	CPA246064V5
1778	CPA247264V5PKG

### Optional Accessories

- Corner Connector Sets
- Bottom Shelf Dunnage Stands (Low or Tall)
- Shelf Identification Tags
- Wall Fastener
- Seismic Foot
- Shelf Divider Panel
- Shelf Divider Bars (Straight or Angled)
- Shelf Rails
- Single Shelf Sheet Pan/Tray Rack
- Single Shelf Security Cage
- Full Wrap Security Cage
- Shelf Traverses (Single or Double)
- Drying and Storage Cradles

### Architect Specs

Posts and Traverses: Internal steel core, reinforced polypropylene exterior.  
 Post Connectors: Reinforced polypropylene.  
 Shelf Plates: Reinforced polypropylene with permanent, molded-in Camguard® antimicrobial.  
 Corner Connectors: Reinforced nylon.  
 Adjustable Foot: Reinforced nylon.

### Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Security Cages, Single Shelf Sheet Pan/Tray Rack, Shelf Rails, Divider Bars, High Density Track and Extension Kits are not NSF Listed.

**CAMBRO**  
TRUSTED FOR GENERATIONS™  
www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.

CAMBRO U.S.A.  
TEL: 1(714) 848-1555  
FAX: 1(714) 230-4375  
international@cambro.com

CPPM1

© Copyright Cambro Manufacturing Company. Printed in the U.S.A. REV. 10/18

1001801