

Camshelving® Premium Series

Stationary Starter & Add-On Units 4 Solid or 4 Vented and Solid Shelves (3 vented + 1 solid)

HEIGHT	DEPTHS	LENGTHS	
1	3	8	
1830 mm	460 mm	610 mm	1220 mm
	540	765	1375
	610	915	1525
		1070	1830

- **Starter Units include:**
2 factory assembled post kits and 8 or 10 traverses and shelf plates.
 - **Add-On Units include:**
1 factory assembled post kit and 8 or 10 traverses and shelf plates.
- Units ship complete in 1 box.

Features & Benefits

- Modular, hygienic, stable and durable, Camshelving Premium Series Shelving is perfect for use in high-volume operations with constant loading of heavy products and frequent daily deliveries.
- Withstands storage temperatures from -38°C to 88°C. Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Impervious to moisture, chemicals, salt, food acids, and humidity.
- Install solid shelf on bottom to prevent water/cleaning liquid from splashing onto products. Install on top to protect product on lower shelves from cooler condensation.
- Posts and traverses have a steel core and smooth polypropylene exterior for superior strength and durability.
- Removable polypropylene shelf plates have permanent, molded-in Camguard, an antimicrobial technology that inhibits the growth of mold, fungus and bacteria.
- Fast assembly. Shelves connect and can be adjusted easily on the dovetails molded into posts every 100 mm. Adjustable foot to level units +/- 15 mm.
- Shelving units interconnect in straight lines with shared posts. Weight bearing is uncompromised and space is maximized. Possible configuration in "L", "U", "T" or "Cross" layouts using corner connectors.
- Posts, traverses and shelf plates wipe clean or can be run through a dishwasher.
- Lifetime warranty against rust and corrosion.
- Available in 1 color – Speckled Gray (480).

Project _____

Item No. _____

Model No. _____

Quantity _____

camguard
ANTIMICROBIAL SHELF PLATES

StoreSafe
STORE FRESH



Stationary Starter Unit



Stationary Add-On Unit

Premium Series Weight Bearing Capacity

Weight must be evenly distributed across the entire shelf.

		UNIT LENGTH 610 – 1220 MM	UNIT LENGTH 1375 – 1830 MM
SINGLE UNIT	Unit only	910 kg	910 kg
	Shelf only	365	275
	Unit with dunnage stand*	1110	1045
	Bottom shelf with dunnage stand*	545	410
CORNER UNIT** With 2 Dunnage Stands required	Unit only	820	—
	Shelf only	185	—
	Bottom shelf with dunnage stands*	275	—
MOBILE UNIT	Unit only***	340	—

* Dunnage Stands add stability and increase weight bearing capacity on bottom shelf only. Add to any shelf length. Highly recommended for Starter Units 1375 mm and longer, all Corner Units, U-Shape Units and units specified for heavier loads.

** Corner connectors are for use only with shelves 610 - 1220 mm long.

*** Due to the weight bearing capacity of casters, maximum weight load on an entire Mobile Unit is 340 kg.

Approvals




Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Security Cages, Single Shelf Sheet Pan/Tray Rack, Shelf Rails, Divider Bars, High Density Track and Extension Kits are not NSF Listed.

Camshelving® Premium Series

Stationary Starter & Add-On Units 4 Solid or 4 Vented and Solid Shelves (3 vented + 1 solid)

1830
mm
HEIGHT

S4 4-Shelf Solid Units



460 mm
DEPTH

LENGTH	CODE
610 mm	CPU182472S4
765	CPU183072S4
915	CPU183672S4
1070	CPU184272S4
1220	CPU184872S4
1375	CPU185472S4
1525	CPU186072S4
1830	CPU187272S4PKG

LENGTH	CODE
565 mm	CPA182472S4
718	CPA183072S4
870	CPA183672S4
1023	CPA184272S4
1175	CPA184872S4
1328	CPA185472S4
1480	CPA186072S4
1778	CPA187272S4PKG

540 mm
DEPTH

610 mm	CPU212472S4
765	CPU213072S4
915	CPU213672S4
1070	CPU214272S4
1220	CPU214872S4
1375	CPU215472S4
1525	CPU216072S4
1830	CPU217272S4PKG

565 mm	CPA212472S4
718	CPA213072S4
870	CPA213672S4
1023	CPA214272S4
1175	CPA214872S4
1328	CPA215472S4
1480	CPA216072S4
1778	CPA217272S4PKG

610 mm
DEPTH

610 mm	CPU242472S4
765	CPU243072S4
915	CPU243672S4
1070	CPU244272S4
1220	CPU244872S4
1375	CPU245472S4
1525	CPU246072S4
1830	CPU247272S4PKG

565 mm	CPA242472S4
718	CPA243072S4
870	CPA243672S4
1023	CPA244272S4
1175	CPA244872S4
1328	CPA245472S4
1480	CPA246072S4
1778	CPA247272S4PKG

Color: Speckled Gray (480).

Due to the unit weight, PKG units ship in separate cartons. Post kits require assembly.

Project _____

Item No. _____

Model No. _____



Quantity _____

VS4

4-Shelf Units (3 Vented + 1 Solid)

Starter

Add-On



LENGTH	CODE
610 mm	CPU182472VS4
765	CPU183072VS4
915	CPU183672VS4
1070	CPU184272VS4
1220	CPU184872VS4
1375	CPU185472VS4
1525	CPU186072VS4
1830	CPU187272VS4PKG

LENGTH	CODE
565 mm	CPA182472VS4
718	CPA183072VS4
870	CPA183672VS4
1023	CPA184272VS4
1175	CPA184872VS4
1328	CPA185472VS4
1480	CPA186072VS4
1778	CPA187272VS4PKG

610 mm	CPU212472VS4
765	CPU213072VS4
915	CPU213672VS4
1070	CPU214272VS4
1220	CPU214872VS4
1375	CPU215472VS4
1525	CPU216072VS4
1830	CPU217272VS4PKG

565 mm	CPA212472VS4
718	CPA213072VS4
870	CPA213672VS4
1023	CPA214272VS4
1175	CPA214872VS4
1328	CPA215472VS4
1480	CPA216072VS4
1778	CPA217272VS4PKG

610 mm	CPU242472VS4
765	CPU243072VS4
915	CPU243672VS4
1070	CPU244272VS4
1220	CPU244872VS4
1375	CPU245472VS4
1525	CPU246072VS4
1830	CPU247272VS4PKG

565 mm	CPA242472VS4
718	CPA243072VS4
870	CPA243672VS4
1023	CPA244272VS4
1175	CPA244872VS4
1328	CPA245472VS4
1480	CPA246072VS4
1778	CPA247272VS4PKG

Optional Accessories

- Corner Connector Sets
- Bottom Shelf Dunnage Stands (Low or Tall)
- Shelf Identification Tags
- Wall Fastener
- Seismic Foot
- Shelf Divider Panel
- Shelf Divider Bars (Straight or Angled)
- Shelf Rails
- Single Shelf Sheet Pan/Tray Rack
- Single Shelf Security Cage
- Full Wrap Security Cage
- Shelf Traverses (Single or Double)
- Drying and Storage Cradles

Architect Specs

Posts and Traverses: Internal steel core, reinforced polypropylene exterior.
Post Connectors: Reinforced polypropylene.
Shelf Plates: Reinforced polypropylene with permanent, molded-in Camguard® antimicrobial.
Corner Connectors: Reinforced nylon.
Adjustable Foot: Reinforced nylon.

Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Security Cages, Single Shelf Sheet Pan/Tray Rack, Shelf Rails, Divider Bars, High Density Track and Extension Kits are not NSF Listed.

CAMBRO
TRUSTED FOR GENERATIONS™
www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.

CAMBRO U.S.A.
TEL: 1(714) 848-1555
FAX: 1(714) 230-4375
international@cambro.com

CPPM4

© Copyright Cambro Manufacturing Company. Printed in the U.S.A. REV. 10/18

10018001