

Camshelving® Premium Series

Stationary Starter & Add-On Units 4 or 5 Vented Shelves

HEIGHT	DEPTHS	LENGTHS	
1	3	8	
1830 mm	460 mm	610 mm	1220 mm
	540	765	1375
	610	915	1525
		1070	1830

- **Starter Units include:**
2 factory assembled post kits and 8 or 10 traverses and shelf plates.
 - **Add-On Units include:**
1 factory assembled post kit and 8 or 10 traverses and shelf plates.
- Units ship complete in 1 box.

Features & Benefits

- Modular, hygienic, stable and durable, Camshelving Premium Series Shelving is perfect for use in high-volume operations with constant loading of heavy products and frequent daily deliveries.
- Withstands storage temperatures from -38°C to 88°C. Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Impervious to moisture, chemicals, salt, food acids, and humidity.
- Posts and traverses have a steel core and smooth polypropylene exterior for superior strength and durability.
- Removable polypropylene shelf plates have permanent, molded-in Camguard, an antimicrobial technology that inhibits the growth of mold, fungus and bacteria.
- Fast assembly. Shelves connect and can be adjusted easily on the dovetails molded into posts every 100 mm. Adjustable foot to level units +/- 15 mm.
- Shelving units interconnect in straight lines with shared posts. Weight bearing is uncompromised and space is maximized. Possible configuration in "L", "U", "T" or "Cross" layouts using corner connectors.
- Posts, traverses and shelf plates wipe clean or can be run through a dishwasher.
- Lifetime warranty against rust and corrosion.
- Available in 1 color – Speckled Gray (480).

Project _____

Item No. _____

Model No. _____

Quantity _____

camguard
ANTIMICROBIAL SHELF PLATES

StoreSafe
STORE FRESH



Stationary Starter Unit

Stationary Add-On Unit

Premium Series Weight Bearing Capacity

Weight must be evenly distributed across the entire shelf.

		UNIT LENGTH 610 – 1220 MM	UNIT LENGTH 1375 – 1830 MM
SINGLE UNIT	Unit only	910 kg	910 kg
	Shelf only	365	275
	Unit with dunnage stand*	1110	1045
	Bottom shelf with dunnage stand*	545	410
CORNER UNIT** With 2 Dunnage Stands required	Unit only	820	—
	Shelf only	185	—
	Bottom shelf with dunnage stands*	275	—
MOBILE UNIT	Unit only***	340	—

* Dunnage Stands add stability and increase weight bearing capacity on bottom shelf only. Add to any shelf length. Highly recommended for Starter Units 1375 mm and longer, all Corner Units, U-Shape Units and units specified for heavier loads.

** Corner connectors are for use only with shelves 610 - 1220 mm long.

*** Due to the weight bearing capacity of casters, maximum weight load on an entire Mobile Unit is 340 kg.

Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Security Cages, Single Shelf Sheet Pan/Tray Rack, Shelf Rails, Divider Bars, High Density Track and Extension Kits are not NSF Listed.

Camshelving® Premium Series

Stationary Starter & Add-On Units 4 or 5 Vented Shelves

Project _____

Item No. _____



Model No. _____

Quantity _____

V4

1830
mm
HEIGHT

4-Shelf Vented Units





460
mm
DEPTH

LENGTH	CODE
610 mm	CPU182472V4
765	CPU183072V4
915	CPU183672V4
1070	CPU184272V4
1220	CPU184872V4
1375	CPU185472V4
1525	CPU186072V4
1830	CPU187272V4PKG

LENGTH	CODE
565 mm	CPA182472V4
718	CPA183072V4
870	CPA183672V4
1023	CPA184272V4
1175	CPA184872V4
1328	CPA185472V4
1480	CPA186072V4
1778	CPA187272V4PKG

V5

5-Shelf Vented Units



LENGTH	CODE
610 mm	CPU182472V5
765	CPU183072V5
915	CPU183672V5
1070	CPU184272V5
1220	CPU184872V5
1375	CPU185472V5
1525	CPU186072V5
1830	CPU187272V5PKG

LENGTH	CODE
565 mm	CPA182472V5
718	CPA183072V5
870	CPA183672V5
1023	CPA184272V5
1175	CPA184872V5
1328	CPA185472V5
1480	CPA186072V5
1778	CPA187272V5PKG

540
mm
DEPTH

610 mm	CPU212472V4
765	CPU213072V4
915	CPU213672V4
1070	CPU214272V4
1220	CPU214872V4
1375	CPU215472V4
1525	CPU216072V4
1830	CPU217272V4PKG

565 mm	CPA212472V4
718	CPA213072V4
870	CPA213672V4
1023	CPA214272V4
1175	CPA214872V4
1328	CPA215472V4
1480	CPA216072V4
1778	CPA217272V4PKG

610 mm	CPU212472V5
765	CPU213072V5
915	CPU213672V5
1070	CPU214272V5
1220	CPU214872V5
1375	CPU215472V5
1525	CPU216072V5
1830	CPU217272V5PKG

565 mm	CPA212472V5
718	CPA213072V5
870	CPA213672V5
1023	CPA214272V5
1175	CPA214872V5
1328	CPA215472V5
1480	CPA216072V5
1778	CPA217272V5PKG

610
mm
DEPTH

610 mm	CPU242472V4
765	CPU243072V4
915	CPU243672V4
1070	CPU244272V4
1220	CPU244872V4
1375	CPU245472V4
1525	CPU246072V4
1830	CPU247272V4PKG

565 mm	CPA242472V4
718	CPA243072V4
870	CPA243672V4
1023	CPA244272V4
1175	CPA244872V4
1328	CPA245472V4
1480	CPA246072V4
1778	CPA247272V4PKG

610 mm	CPU242472V5
765	CPU243072V5
915	CPU243672V5
1070	CPU244272V5
1220	CPU244872V5
1375	CPU245472V5
1525	CPU246072V5
1830	CPU247272V5PKG

565 mm	CPA242472V5
718	CPA243072V5
870	CPA243672V5
1023	CPA244272V5
1175	CPA244872V5
1328	CPA245472V5
1480	CPA246072V5
1778	CPA247272V5PKG

Color: Speckled Gray (480).

Due to the unit weight, PKG units ship in separate cartons. Post kits require assembly.

Optional Accessories

- Corner Connector Sets
- Bottom Shelf Dunnage Stands (Low or Tall)
- Shelf Identification Tags
- Wall Fastener
- Seismic Foot
- Shelf Divider Panel
- Shelf Divider Bars (Straight or Angled)
- Shelf Rails
- Single Shelf Sheet Pan/Tray Rack
- Single Shelf Security Cage
- Full Wrap Security Cage
- Shelf Traverses (Single or Double)
- Drying and Storage Cradles

Architect Specs

Posts and Traverses: Internal steel core, reinforced polypropylene exterior.
 Post Connectors: Reinforced polypropylene.
 Shelf Plates: Reinforced polypropylene with permanent, molded-in Camguard® antimicrobial.
 Corner Connectors: Reinforced nylon.
 Adjustable Foot: Reinforced nylon.

Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Security Cages, Single Shelf Sheet Pan/Tray Rack, Shelf Rails, Divider Bars, High Density Track and Extension Kits are not NSF Listed.

CAMBRO
TRUSTED FOR GENERATIONS™
www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.

CAMBRO U.S.A.
TEL: 1(714) 848-1555
FAX: 1(714) 230-4375
international@cambro.com

CPPM3

© Copyright Cambro Manufacturing Company. Printed in the U.S.A. REV. 10/18

1001801