

# Pro Cart Ultra®

ELECTRIC & NON-ELECTRIC INSULATED HOLDING & TRANSPORT CABINETS



- ✓ Hold and transport hot and cold foods in a single cart.
- ✓ Maintains food quality and moisture.
- ✓ Keep food safe while unplugged 4 hours.
- ✓ Change hot to cold or cold to hot with a simple hardware change.

**CAMBRO**  
TRUSTED FOR GENERATIONS™

[www.cambro.com](http://www.cambro.com)

# The One-of-a-Kind Pro Cart Ultra®

## The Most Adaptable Insulated Holding and Transport Carts on the Market

The Pro Cart Ultra is the ultimate food transport cart that can hold all your hot and cold menu items in the same cart, at the same time—without a compressor! It even holds food safely while unplugged up to 4 hours.

## The Pro Cart Ultra Comes Configured Just How You Want it

1. Choose the tall, two compartment model, or the low, single-compartment model.
2. Specify electric hot, electric cold or non-electric (passive) holding in each compartment.
3. Universal rails fit food pans, sheet pans and more.



## Capacity per Compartment




TYPE OF CONTAINER	STANDARD CAPACITY	STANDARD RAIL SPACING	MAXIMUM CAPACITY	MAXIMUM CAPACITY RAIL SPACING
FULL SIZE SHEET PANS 45,7 x 66 CM	8	7,6 cm	16*	3,8 cm
HALF SIZE SHEET PANS 33 x 45,7 CM	16	7,6 cm	32*	3,8 cm
GN 1/1 HOTEL PANS 6,5 CM DEEP	16	7,6 cm	16	7,6 cm
GN 1/1 HOTEL PANS 10 CM DEEP	10	11,4 cm	10	11,4 cm
EURO BAKING SHEETS 60 x 40 CM	8	7,6 cm	16*	3,8 cm
BASKETS 33 x 45,7 CM	16	7,6 cm	16	7,6 cm
PIZZA BOXES 40,6 x 40,6 x 5,1 CM	8	7,6 cm	8	7,6 cm

Standard rails: 8 rails / cart \*Additional rails required.


# Non-Electric (Passive)



**Hot** — Temperature loss averaging 1,5°C per hour.




**Cold** — Temperature gain averaging 0,4°C per hour.



## Pro Cart Ultra® Features

All Models:



**Insulation:** CFC-free, polyurethane insulation throughout the body and doors maximizes heat or cold retention for 4 hours or more with no electricity needed.



**10 cm Nylon Latches:** For easy opening and closing and to secure contents during transport. Door is lockable.




**Stainless Steel Hinge:** For long term durability.



**Solar Digital Thermometer:** Monitor internal cabinet temperature at a glance.

# Electric



**Polyethylene Exterior:** Keeps food moist naturally and remains cool to the touch during operation, unlike metal cabinets.



**Gasket-free Door:** For easy cleaning and fewer replacement parts. Door opens full 270°.



**12,7 x 20,3 cm Menu Pocket:** Allows for easy product ID with either an index card or by writing directly onto smooth surface with a grease pencil.



**Standard 15,2 x 5,1 cm Heavy Duty Casters:** Two non-marking, high-performance, swivel casters with brakes in the front and two rigid casters in the back for smooth positioning and navigation.



## Electric Models Only



**Cord Keeper:** Safely and securely stores detachable 2,7 m power cord.

## COLD

Digital controller allows cold to be set from 0,3° to 4,4°C.

### **THERMOELECTRIC COOLING COOLS DOWN TO 0,3°C**

without a compressor for the ultimate in cold mobility and food safety on the go. Note: Operate in 32,2°C or less ambient temperature for best results.

**Pre-chill time:** 90 minutes to 4,4°C. (Tested at 23°C ambient.)

**Recovery time:** 10 minutes after door open for 30 seconds.

## HOT

Keeps food safely between 65,5° to 74°C with convenient, pre-set, gentle, non-radiant heat.

### **CONVECTION HEAT LESS THAN 5 AMPS**

Gentle, non-radiant heat circulates consistently from front to back of the cabinet.

**Pre-heat time:** 45 minutes.

**Recovery time:** 3 minutes after door open for 30 seconds.

# Change is Good!

All Pro Cart Ultra® models feature non-electric (passive), active hot or active cold modules that can easily be removed and replaced with a different module to support menu or operational changes—a great way to stretch budget dollars with a single piece of equipment.

## Just 5 Minutes to Change Module

1. Seasonal menus
2. Menu changes
3. Additional budget availability
4. Different location or facility
5. New trends



Interior with Cold module



Exterior back with Cold module



Interior with Hot module



Exterior back with Hot module



## Powerful Performance, Low Power Consumption



- ✓ Energy efficient, active modules draw less than 5 amps each.
- ✓ Cold module uses environmentally friendly, thermoelectric technology.
- ✓ Plugs into a standard outlet.

### Electrical Specifications (Per Compartment)

	HOT 110V	HOT 220V	COLD
REQUIRED VOLTAGE	100-125 VAC	200-230 VAC	100-230 VAC
MAXIMUM AMP	4.6a	2.3a	3.26a, 1.42a
WATTS / HEATER OR COOLER	529w	506w	326.6w
HERTZ	50/60	50/60	50/60
PHASE	Single	Single	Single
ALTERNATE PLUG TYPES AVAILABLE FOR THESE COUNTRIES	US, Canada, Mexico, China Europe, UK, Ireland, Australia, South Africa, Japan		
POWER CORD LENGTH	2,7 m		

\* If country is not listed, please call Cambro Customer Service for details.

# Pro Cart Ultra® Model Specifications

	CODE	DESCRIPTION	UNIT WEIGHT
	<b>TALL PROFILE</b>		
	<b>Both Compartments Passive (Non-electric)</b>		
	PCUPP	Both compartments non-electric / passive	106,7 kg
	<b>Both Compartments Hot</b>		
	PCUHH	110V standard	121,3
	PCUHH2*	220V standard	121,7
	<b>Both Compartments Cold</b>		
	PCUCC	110V standard	126,3
	PCUCC2*	220V standard	128,7
	<b>Combination Hot &amp; Cold</b>		
	PCUHC	Top compartment hot, bottom cold. 110V standard	122,9
	PCUCH	Top compartment cold, bottom hot. 110V standard	122,9
	PCUHC2*	Top compartment hot, bottom cold. 220V standard	123,3
	PCUCH2*	Top compartment cold, bottom hot. 220V standard	123,3
<b>Combination Passive &amp; Hot or Cold</b>			
PCUPH	Top compartment passive, bottom hot. 110V standard	155,8	
PCUPC	Top compartment passive, bottom cold. 110V standard	188,3	
PCUPH2*	Top compartment passive, bottom hot. 220V standard	116	
PCUPC2*	Top compartment passive, bottom cold. 220V standard	119,5	
	<b>LOW PROFILE</b>		
	PCULP	Non-electric / passive	63,5
	PCULH	Hot Cart, 110V standard	68,5
	PCULC	Cold Cart, 110V standard	70,8
	PCULH2*	Hot Cart, 220V standard	68,5
	PCULC2*	Cold Cart, 220V standard	70,8

Color: Charcoal Gray (615). **Standard Railing Includes:** 8 pairs of stainless steel Universal rails/compartments.

**Includes Standard Casters:** 15 x 5 cm heavy duty swivel with brake in front, rigid in back.

\* For Australia, please add AUS at the end of the product code. For UK, please add UK at the end of the product code.

For Europe, please add EU at the end of the product code. For South Africa, please add SA at the end of the product code.

## Unit Dimensions

UNIT	EXTERIOR DIM. W x D x H	COMPARTMENT DIM. W x D x H
<b>Tall Profile</b>		
COLD	71,1 x 92,7 x 167,6 cm	53,7 x 66,7 x 64,8 cm
HOT / PASSIVE	71,1 x 90,8 x 167,6	53,7 x 68,6 x 64,8
<b>Low Profile</b>		
COLD	71,1 x 92,7 x 101,6	53,3 x 68,6 x 64,8
HOT / PASSIVE	71,1 x 90,8 x 101,6	53,7 x 68,6 x 64,8

## Optional Accessories

CODE	DESCRIPTION
PCMH / PCMH2	Hot module unit 110V / 220V
PCMC / PCMC2	Cold module unit 110V / 220V
SSR1	1 Pair of Rails
SSR8	8 Pairs of Rails

Color: (000). PCMH / PCMH2 and PCMC / PCMC2 Color: Charcoal Gray (615).



Passive and/or Hot Models

## Security Package (SP)

Specially designed for operations where safety and security are a top priority. To order add SP after the product code.

- ✓ Tamper resistant fasteners secure side column panels to the cart.
- ✓ Cross locking rods behind column panels lock 5 rails in place.
- ✓ Each compartment holds ten 10 cm deep hotel pans.
- ✓ Passive and electrical modules and cord strap keepers are secured in place with tamper resistant fasteners.
- ✓ Non removable doors. Lockable hasp secures both doors at once. (Lock not included).
- ✓ Heavy duty casters mounted with tamper resistant fasteners.



CAMBRO U.S.A.  
TEL: 1(714) 848-1555  
FAX: 1(714) 230-4375  
international@cambro.com

CAMBRO EUROPEAN LOGISTICS  
TEL: (49) 7022 90 100 0  
FAX: (49) 7022 90100 19  
cambroeurope@cambro.com

CAMBRO UK  
TEL: 0800 587 0057 Toll Free  
FAX: 0845 280 3411  
cambrouk@cambro.com

CAMBRO IRELAND  
TEL: 1800 509 046 Toll Free  
FAX: 01 633 55 76  
cambroireland@cambro.com

© Copyright Cambro Manufacturing Company. Printed in the U.S.A.

LITX19PCUEN