



PRODUCT SPECS

# ESSENTIAL 2

## TABLE BASE

### Features

- Full table base  
(add your own work surface)
- Meets BIFMA X5.5 standards
- UL 962 approved
- Easy-order with one part number
- Optional gyro sensor





## STANDARD SPECIFICATIONS

- Single stage height range 26" –45" (without top)
- Dual stage height range 21.75" –47.75" (without top)
- Fits both 24" and 30" tops
- Raise/lower speed of 1.375" per second
- Standard base widths 48" –72" (anti-sag bar recommended for widths over 60")
- Power consumption <0.3W
- Available in black, white or silver

## OPTIONS

### HANDSWITCH OPTIONS




Basic Up-Down



Programmable


### POWDER COAT COLOR OPTIONS



Black



White



Silver

### FOOT OPTIONS



T Foot



C Foot

### WARRANTY INFORMATION

**Three Years** Electronic components such as control boxes, handswitches, motors.

**Five Years** Mechanical components such as crank drives, spindles.

**Ten Years** Structural components such as beams, feet and top supports.

## TECHNICAL SPECIFICATIONS

TYPE	STROKE LENGTH (IN)	HEIGHT MIN/MAX (IN)	TRAVEL SPEED (IN/sec)	MAX RATED LOAD (LB)	MAX FUNCTIONAL LOAD (LB)	NOISE LEVEL (DB)
Single Stage (SSE)	19	26/45	1.375	250	306	<50
Dual Stage (DSL)	26	21.75/47.75	1.375	250	306	<50

## STANDARD DIMENSIONS

