



## 15120 Procedure Mask

### Intended Use

Intended to be used in environments where low fluid exposure is a risk.



### Complies with ASTM F2100

Fluid Resistance (mmHg): 80  
BFE (%) @ 3.0  $\mu\text{m}$ :  $\geq 95\%$   
PFE (%) @ 0.1  $\mu\text{m}$ :  $\geq 95\%$   
 $\Delta P$  (mm H<sub>2</sub>O/cm<sup>2</sup>):  $< 4$   
Flame Spread: Class 1

### Key Features

- Complies with ASTM F2100 Level 1 requirements
- Specially designed inner facing improves comfort
- Integrated layers work together to maximize breathability
- Soft comfortable earloops provide easier donning
- Made in North America
- Not made with natural rubber latex

# Procedure Mask

Intended to be used in environments where low fluid exposure is a risk.



## Technical Specifications

Part No.	15120
Description	Procedure Mask
Color	Blue
Fluid Resistance	80 mm Hg
Filtration – BFE	≥98.4
Filtration – PFE	≥97.7
Delta P	≤3.5
Flammability	Class 1
Attachment Design	Earloop
Mask Construction	Sonic Welded
Qty	50/Box, 10/Boxes, 500/Case

Precept® is a registered trademark of Aspen Surgical Products, Inc.

Aspen Surgical reserves the right to make changes without notice in design, specifications and model.

©2021 Aspen Surgical Products, Inc. ALL RIGHTS RESERVED.  
M-SM-CAT-1051517 rev 1 29-JUN-2021 ENG – US

**Aspen Surgical Products, Inc.**  
phone +1 616.698.7100 toll-free +1 888.364.7004  
[aspensurgical.com](http://aspensurgical.com)

