

Solstice Tier 2 Peripheral Devices

Mersive tested the following devices for Solstice video conferencing with the listed versions of Solstice and device firmware. They have been certified for use with top video conferencing services on supported versions of Windows. Mac users should select one of the devices marked as supported on Mac. Tier 2 devices may not be retested with every version of Solstice.

See the Solstice Supported Peripherals list for peripheral devices currently supported for video conferencing with Solstice.

Device Name	Part #	Туре	Latest Tested Firmware	Latest Tested Solstice Version	Notes	Мас	
AMX Acendo Vibe (ACV-5100)	FG4151-00BL -UA/EK (Black), FG4151-00G R-UA/EK (Grey)	videobar	MCU: 3.1.2 DSP: 7.11.0.13 BT: 1.35 HDMI: 01.01.02	6.1	Use USB audio device prioritization to select the built-in mic for video conference audio.		
AVer Cam 540	COMSCA540	camera	0.0.6004.20	6.1		•	
AVer Cam 520 Pro	COM520PRS	camera	0.0.1006.24	6.1			
AVer Cam 520 Pro 2	COM520PR2	camera	0.0.7204.22	6.1			
AVer VB342+ Soundbar	COMVB342+	videobar	0.0.0004.08	6.1			
Avonic CM22	AV-CM22- VCU	webcam	O20.A2_V8. 4.123_24M	6.1	Pair with USB speak- erphone to avoid a po- tential remote echo.		
Avonic CM44	AV-CM44- VCUC-B	webcam		6.1			
ClearOne UNITE 50	910-2100-006	webcam		6.1	Pair with USB speak- erphone to avoid a po- tential remote echo.		
Crestron UC-SB-1- CAM	UC-SB1-CAM	videobar	1.6.12	6.1	Connect camera to dedicated power supply.		
Huddle- CamHD Pro EPTZ	HC-EPTZ- USB	camera	8.2.85	6.1	Camera may not be selectable in video conference when occupancy sensing is enabled. Pair with USB speakerphone to avoid a potential remote echo.		
Huddle- CamHD 3XA	HC3XA-BK (Black), HC3XA-WH (White)	webcam	4.2.5	6.1	Pair with USB speak- erphone to avoid a po- tential remote echo.		
Jabra Speak 810	7810-109, 7810-209, 7810-199, or 7810-299	speaker- phone	1.9.0	6.1			
Jabra Speak 750	7700-409	speaker- phone	2.24.0	6.1			
Konftel Cam20	931201001	webcam	10.0.05	6.1			
Logitech Conference- Cam Con- nect	960-001013	camera	1.1.695	6.1	Requires powered USB hub or power supply. Application-based Log- itech RightSense func- tionality not supported.		



Device Name	Part#	Туре	Latest Tested Firmware	Latest Tested Solstice Version	Notes	Мас	
Logitech BCC950	960-000866	webcam	7.61.1001	6.1	Application-based Log- itech RightSense func- tionality not supported.		
Lumens VC- B11U	VC-B11U	webcam	5.3.1	6.1			
Lumens MS-10	MS-10	videobar	5.1.5	6.1			
Lumens VC- B10U	VC-B10U	camera		6.1	Set camera to ISO mode using dip switches.		
Neets 4K Webcam	325-0100	webcam		6.1	Pair with USB speak- erphone to avoid a po- tential remote echo.	•	
Nureva HDL 300	HDL300-B (Black), HDL300-W (White)	soundbar	2.5.72	6.1	Application-based Nur- eva Cloud Console management not sup- ported.		
Nureva HDL 200	HDL200-B (Black), HDL200-W (White)	soundbar	1.4.72798	6.1	Application-based Nur- eva Cloud Console management not sup- ported.		
Owl Labs Meeting Owl	MTW100	camera	3.2.0.4	6.1		•	
Poly Ea- gleEye Cube	7230-61960-0 01	camera	1.3.1-00126 7	6.1	Running a Poly device management app during a video conference may result in a frozen video feed. Mersive recommends running these apps only when not using the device.		
Vaddio Hud- dle Shot	999-50707-00 0	videobar	1.4.1	6.1		•	
Yamaha YVC-330	10-YVC330	speaker- phone	1.2	6.1			